
SanRex®

TRIAC
For High Temperature

TMG40CQ60L


$I_{T(RMS)}$ =40A, V_{DRM}=600V, Tj=150°C

SanRex Triac **TMG40CQ60L** is specially designed for use in high temperature environment. Thanks to SanRex's new isolated diffusion technology, the **TMG40CQ60L** increases Tj(max) from 125°C to 150 °C. This advantage reduces the needed heat sink size or eliminate the heat sink. Reducing cooling parts contributes not only to lower cost but also high efficiency and reliability.



Non-isolated TO-3P Package

Features
* Glass-passivated junctions features
* High surge Current
* Low voltage drop
* Lead-free solder plated terminals



Internal schematic diagram

Typical Applications
* Home Appliances
* Heater Controls
* Lighting Controls
* Temperature Controls

< Maximum Ratings> (Tj = 25°C unless otherwise noted)


Symbol	Item	Conditions	Ratings	Unit
V_{DRM}	Repetitive Peak Off-state Voltage		600	V
$I_{T(RMS)}$	R.M.S. On-state Current	T_C = 122°C	40	A
I_{TSM}	Surge On-state Current	One cycle, 60Hz, Peak, non-repetitive	420	A
I^2t	I^2t (for fusing)	Value for one cycle surge current	730	A^2s
P_{GM}	Peak Gate Power Dissipation		10	W
$P_{G(AV)}$	Average Gate Power Dissipation		1	W
I_{GM}	Peak Gate Current		3	A
V_{GM}	Peak Gate Voltage		10	V
Tj	Operation Junction Temperature		-40 to +150	°C
T_{stg}	Storage Temperature		-40 to +150	°C
	Mass	Typical Value	5.1	g

SanRex 50 Seaview Blvd. Port Washington, NY 11050-4618 PH.(516)625-1313 FAX(516)625-8845 Web : www.sanrex.com

TRIAC TMG40CQ60L

< Electrical Characteristics > (Tj= 25°C unless otherwise noted)

Symbol	Item		Conditions	Ratings			Unit
				Min.	Typ.	Max.	
I_{DRM}	Repetitive Peak Off-state Current		T_j = 150°C, $V_D = V_{DRM}$, Single Phase, Half wave			8	mA
V_{TM}	Peak On-State Voltage		I_T =60A, Instant measurement			1.4	V
$I_{GT}1^+$	QI	Gate Trigger Current	V_D = 6V, I_T = 1A			50	mA
$I_{GT}1^-$	QII					50	mA
$I_{GT}3^+$	QIV					-	mA
$I_{GT}3^-$	QIII					50	mA
$V_{GT}1^+$	QI	Gate Trigger Voltage	V_D = 6V, I_T = 1A			1.5	V
$V_{GT}1^-$	QII					1.5	V
$V_{GT}3^+$	QIV					-	V
$V_{GT}3^-$	QIII					1.5	V
V_{GD}	Non-Trigger Gate Voltage		Tj = 150°C, V_D=1/2V_{DRM}	0.1			V
(dv/dt)c	Critical Rate of Rise of Commutation Voltage		Tj = 150°C, V_D=2/3V_{DRM}, (di/dt)c=-20A/ms	5			V/Fs
I_H	Holding Current				35		mA
Rth(j-c)	Thermal Resistance		Junction to case			0.6	°C/W



* Dimensions in millimeters