

GX0-3300L

High Frequency, Tight Stability 3.3V Oscillator with 3225 Package

- High precision with tight stability options
- Wide operating temperature ranges
- High frequency fundamental no multiplier
- Low & medium volumes also available
- Fnable / disable tristate function



CONFIGURABLE OPTIONS	
Parameter	Option Code
Frequency	
Frequency stability	
* see note below	
Any	
±2.5ppm max over -40 to +85°C	Н
±5.0ppm max over -40 to +85°C	G
±10ppm max over -40 to +85°C	F
±20ppm max over -40 to +105°C	D
±25ppm max over -40 to +125°C	А


^{*} Frequency stability is inclusive of calibration @ 25°C, operating temperature range, supply voltage change, load change, shock and vibration. Option H inclusive of calibration @ 25°C and operating temperature range only.



SPECIFICATIONS

Frequency range	10.0 ~ 160MHz				
. , ,					
Dimensions	3.2 x 2.5 x 1.1mm				
Storage temperature	-55 to +125°C				
range					
Supply voltage (V _{DD})	+3.3V (±5%)				
Supply current	11mA max (10.0 ~ 80.0MHz)				
	20mA max (80.0 ~ 160MHz)				
Logic levels	'0' level = 10%V _{DD} max				
	'1' level = 90%V _{DD} min				
Start up time	5ms max				
Waveform symmetry	45:55 max @ 50%V _{DD}				
Driving ability	15pF CMOS				
Rise / fall time	6ns max (≤40.0MHz)				
(10~90%V _{DD})	3ns max (>40.0MHz)				
Enable / disable function	Tristate (control via pad 1)				
Stand-by current	10μA max				
Phase jitter RMS	0.3ps typ (12kHz ~ 20.0MHz)				

PACKAGE DRAWING



PAD	CONNECTION
1	Enable / disable
2	Ground
3	Output
4	Supply

Dimensions in mm

ORDERING INFORMATION

To request a quotation for the GXO-3300L please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

ENABLE / DISABLE FUNCTION

Input (pad 1)	Output (pad 3)				
Open	Enabled				
'1' level	Enabled				
'O' level	High Impedance				





MARKING


FREQUENCY DC PART NO

Marking type: Laser


DC = Date Code in YM, eg. "GF" = Jun 2017

		Α	В	С	D	Ε	F	G	Н	J	K	L	М
	Υ	1	2	3	4	5	6	7	8	9	0		
ı	М	Jan	Feb	Mar	Apr	Mav	Jun	Jul	Aug	Sep	Oct	Nov	Dec

SOLDERING PROFILE



TAPE & REEL SPECIFICATION



Dimensions in mm

HANDLING & STORAGE



Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)



CONSTRUCTION

Ceramic body with gold-plated pads Metal lid, seam sealed

MATERIAL COMPOSITION



Lead-free (< 0.1% by weight)



RoHS 2 compliant with no exemptions. See our

declaration



REACH compliant.



Au Ta Sn W Free of conflict minerals. See our declaration



Free of Halogens. See our declaration



 $\label{prop:cone-depleting} \mbox{Free of Ozone-depleting substances}.$ See our

declaration



OTHER INFORMATION

About Golledge

We are the UK's leading supplier of frequency control products and are proud to serve the global electronics industry. Our philosophy is a focus firmly on your requirements by striving to meet and exceed your needs. We do this by ensuring the utmost quality and consistency in our products and services. If you have any queries about the Golledge service or any of our products please get in touch, we'd love to hear from you.

Come and visit

Give us a call

Email us

Eaglewood Park, ILMINSTER, Somerset, TA19 9DQ, England Tel: +44 1460 256 100 Fax: +44 1460 256 101 sales@golledge.com

Our Worldwide Distributors

Belgium & Luxembourg

Alcom Electronics NV/SA



Email Web Tel

info@alcom.be www.alcom.be +32 (0)3 458.30.33

China, Hong Kong - 中国 / 香港

Meiya China



Email Web

sales@meiyatech.com www.meiyatech.com +86 755 2823 1923

France

Equipments Scientifique



Email Web

comp@es-france.com www.es-france.com +33 1 47 95 99 89

Germany

MEV Elektronik Service GmbH



Web

info@mev-elektronik.com www.mev-elektronik.com +49 54 24 23 40-0

India

V5 Semiconductors



Email Web Tel

sales@v5semiconductors.com v5semiconductors.com +91-80-2661 0621

Israel

Phoenix Technologies Ltd



Email Web Tel

sales@phnx.co.il www.phnx.co.il +972 9 764 4800

Netherlands

Alcom Electronics BV



Email Web Tel

info@alcom.nl alcom.nl +31 (0)10 288.25.00

Norway

Link Nordic



bjorn.nyjordet@linknordic.com linknordic.com +47 93 22 68 90

Russia - Россия

EFO Ltd



Email Web Tel

elena@efo.ru www.golledge.ru +7(812)327-8654

Spain & Portugal

R.C. Microelectronica, S.A.



Email Web Tel

ventas@rcmicro.es www.rcmicro.es +34 93 260 21 66

Our customer feedback is testament to our quality; "Never had such good service as this from anyone in 35 years of being in the industry, this is impressive and has really helped us out of a corner to keep the design flowing" Andy (Senior Design Engineer), "As always your support is state of the art" Nicoleta (Material Management), "Legendary work - as usual it has to be said" John (Operations). To take advantage of our highly praised service get in touch with us today.

