



**Specifications:**  
**规格:**  
**Voltage rating:125V AC/DC**  
**额定电压: 125V AC/DC**  
**Current rating:2A AC/DC**  
**额定电流: 2A AC/DC**  
**Withstanding voltage:500V AC/minute**  
**耐受电压: 500V AC/分钟**  
**Temperature range:-40℃--+105℃**  
**温度范围: -40℃--+105℃**  
**Insulation resistance:≥1000MΩ**  
**绝缘电阻: ≥1000MΩ**  
**Contact resistance:≤20mΩ**  
**接触电阻: ≤20mΩ**  
**After environmental testing:≤30mΩ**  
**环境测试后: ≤30兆欧**

**X2081T X - P XXX**  
 ① ② ③ ④ ⑤

- 1.Series Number
- 2.Category:T-terminal
- 3.Shape:Blank-ordinary
- 4.Material:P-Phosphor bronze
- 5.Plating style:SN-Bright tin plating;V01-Gold Flash

X2081T-PSN	phosphor Bronze	AWG#22-28	1.4mm(Max)	15u"Ni;70u" Sn	X2081H
PART NO	Material	Wire Range	Insulation OD	Finish	Suitable XKB Terminal

					units: mm	DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector		
					tolerance:	DWN		DATE		VIEW:	PART NO.:		
					X.X ±0.2mm	CHKD		DATE		UNIT: mm/in	2.00mm Crimp Style Connectors		
					X.XX ±0.1mm	APPD		DATE		SIZE: A4	DWG NO.:		
					X.XXX ±0.05mm						X2081T-PSN		
REVISIONS					UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO.,LIMITED					WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn										1.0g	1/1	A0	