



U221-04XN-4BU02-XS

- 1:Au 1U"
- 5:Au 15U"
- 6:Au 30U"
- 1:PBT
- 2:PA6T
- 3:PA9T
- 4:LCP
- S:SUS
- S:Scrolls F:Flat
- W:WHITE B:BLACK

Housing Material: LCP 94V-0, black/White
 Contact Terminal: COPPER ALLOY. (T=0.25mm)
 Metallic Shell: SUS
 FINISH:
 2-1. CONTACT: UNDER PLATED 50u" MIN NICKEL ALL AREA.
 100u" MIN TIN IN SOLDER TAIL AREA.
 30u" MIN. GOLD PLATED AT CONTACT AREA.
 2-2. SHELL: NICKEL 50u" MIN. PLATING OVERALL.
 ENVIRONMENTAL CHARACTERISTICS:
 3-1. OPERATION TEMPERATURE RANGE : -10°C TO +85°C.

F: Flat

					ANGLAR	±5°	DSND		DATE		SCALE: N/A	MODEL TYPE: USB 2.0		
Δx					L ≤ 4	±0.2	DWN		DATE		VIEW:	PART NO.:		
Δx					4 < L ≤ 16	±0.3	CHKD		DATE		UNIT: mm/in	DWG NO.:		
Δx					16 < L ≤ 63	±0.4	APPD		DATE		SIZE: A4	U221-04XN-4BU02-XS		
MARK	DESCRIPTION				DATE	REVISED	APPROVED					WEIGHT	SHEET	REVISION
					UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO., LIMITED					1.0g	1/1	A0
REVISIONS														
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn														