



C9900-U332-0010 | Battery pack



i Product status: Regular delivery

All Industrial PCs can be equipped with a 24 V power supply unit and an integrated UPS. The UPS supplies the PC with power if the mains power fails. This allows data to be saved on the hard disk or Flash, after which the PC can be shut down properly. A battery pack, which serves as the energy storage device, is mounted on a DIN rail outside the PC.

Rated at 3.4 Ah, the maintenance-free C9900-U330 24 V battery pack offers a very high nominal capacity in a compact package.

With its rated capacity of 1.2 Ah, the very compact 24 V C9900-U332 battery pack is designed for PCs with Intel Atom® or Intel® Celeron® ULV 827E.

Product information

Technical Data

Technical data	C9900-U332
Type	battery pack for PCs with 24 V power supply with intergrated UPS, 1.2 Ah
Housing	metal housing for mounting on norm rail TS35x15 2.3
Operating temperature	0...+50 °C
Weight	2.1 kg
Dimensions (W x H x D)	68.7 mm x 106.6 mm x 143.8 mm
Nominal voltage	24 V

Nominal Capacity	1.2 Ah (20 h discharge)
Internal structure	two 12 V batteries in series connection
Fuse	9 A by PTC element
Maintenance	maintenance-free
Additional Information	VRLA AGM Technology = valve regulated lead acid batteries with glass fiber mat inside the separator (VRLA = valve regulated lead acid, AGM = absorbed glass mat technology)