


SAW Bandpass Filter 201360B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D2012

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201360B	
		Rev. Date	2005-08-29	
		Rev.	NM4028-CS01	1/5

SAW Bandpass Filter 201360B



3. Specifications

Fo = 140.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	139.85	140.0	140.15
Insertion Loss	dB	-	24.0	25.5
1dB Bandwidth	MHz	-	27.2	-
3dB Bandwidth	MHz	28	28.4	-
40dB Bandwidth	MHz	-	32.9	33.4
Amplitude Ripple (Fo +/- 13.0 MHz)	dB	-	0.6	1.0
Group Delay Variation (Fo +/- 13.0 MHz)	nsec	-	20	50
Absolute Delay	usec	-	1.01	-
Ultimate Rejection	dB	50	52	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201360B	
		Rev. Date	2005-08-29	
		Rev.	NM4028-CS01	2/5

SAW Bandpass Filter 201360B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



5. Marking Configuration

ITF¹⁾05A001²⁾
201360B³⁾

1) Manufacturer name

2) Lot Number



3) Part Number

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201360B	
		Rev. Date	2005-08-29	
		Rev.	NM4028-CS01	3/5

SAW Bandpass Filter 201360B



6. Typical Performance (at +25℃)



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

201360B

Rev. Date





2005-08-29

Rev.

NM4028-CS01

4/5

SAW Bandpass Filter 201360B



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

201360B

Rev. Date

2005-08-29

Rev.

NM4028-CS01

5/5