


Surface Mount Schottky Barrier Rectifier
Reverse Voltage - 40 to 200 V
Forward Current - 20 A
FEATURES

- ◆ High current capability
- ◆ Low forward voltage drop
- ◆ High surge capability
- ◆ High temperature soldering guaranteed
- ◆ Mounting position: any
- ◆ Lead free in comply with EU RoHS 2011/65/EU directives


MECHANICAL DATA

- ◆ Case: TO-263(D²-PAK)
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026
- ◆ Approx. Weight: 1.16g / 0.04oz


TO-263(D²-PAK)
Maximum Ratings and Electrical characteristics

Ratings at 25 ° ambient temperature unless otherwise specified.

Parameter	Symbols	MBR2040CG	MBR2045CG	MBR2060CG	MBR20100CG	MBR20150CG	MBR20200CG	Units		
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	40	45	60	100	150	200	V		
Maximum RMS voltage	V_{RMS}	28	31.5	42	70	105	140	V		
Maximum DC Blocking Voltage	V_{DC}	40	45	60	100	150	200	V		
Maximum Average Forward Rectified Current per diode per device	$I_{F(AV)}$	10 20						A		
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed On Rated Load (JEDEC method)	I_{FSM}	150						A		
Maximum Instantaneous Forward Voltage at 10 A	V_F	0.65		0.70	0.85	0.90	0.92	V		
Maximum DC Reverse Current at Rated DC Reverse Voltage $T_A = 25^\circ C$ $T_A = 125^\circ C$	I_R	0.1 20		0.05 20		0.05 20		mA		
Typical Junction Capacitance ⁽¹⁾	C_j	600		400				pF		
Typical Thermal Resistance ⁽²⁾	$R_{\theta JA}$	45						$^\circ C/W$		
Operating Junction Temperature Range	T_j	-55 ~ +150				-55 ~ +175		$^\circ C$		
Storage Temperature Range	T_{stg}	-55 ~ +150				-55 ~ +175		$^\circ C$		

⁽¹⁾ Measured at 1 MHz and applied reverse voltage of 4 V D.C

⁽²⁾ P.C.B. mounted with 10cm X 10cmX1mm copper pad areas.

Fig.1 TYPICAL FORWARD CURRENT DERATING CURVE




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic(per leg)




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current







Fig.6- Typical Transient Thermal Impedance



Package Outline
TO-263

Marking on the body

Summary of Packing Options

Package	Packing Description	Packing Quantity	Industry Standard
TO-263	Tube	50	EIA-481-1