General Cable Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: C4110A Revision Level: 15 Date: 7/16/2007

15C 22 7/30 TC PVC PVC **COMMUNICATION CABLE**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#22 AWG 7/30 Tinned Copper	0.030" nom.
Insulation:	0.010" Wall Semi-Rigid Polyvinyl Chloride	0.050" nom.
Cable:	15 conductors	0.239" nom.
Jacket:	0.032" Wall Polyvinyl Chloride	0.303" +/- 0.015"
Print Legend:	***CAROL (R) 22 AWG – C4110 – 105C LL69381 CMG CSA C/US OR AWM I/II A/B 105C 600V FT4 OR AWM STYLE 2464 - - MADE IN USA (DATE CODE & SEQ. FOOTAGE)***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
Canadian Electrical Code	CSA 22.2 No. 214
UL Subject 758 (CSA)	AWM Style 2464
CSA International	Type CMG Type AWM

C. ELECTRICAL PROPERTIES

TEMPERATURE:	105 C
SUGGESTED WORKING VOLTAGE (Vrms):	600 Vrms
CONDUCTOR D.C. RESISTANCE:	16.6 Ohms/1000 ft. nom. @ 20 C

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black	11	Blue/Black
2	White	12	Black/White
3	Red	13	Red/White
4	Green	14	Green/White
5	Orange	15	Blue/White
6	Blue		
7	White/Black		
8	Red/Black		
9	Green/Black		
10	Orange/Black		

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.