ZX5T3Z


40V PNP HIGH GAIN LOW SATURATION MEDIUM POWER TRANSISTOR IN SOT89

SUMMARY

BV_{CEO} = -40V : R_{SAT} = 29mΩ; I_C = -5.5A

DESCRIPTION


Packaged in the SOT89 outline this new 5th generation low saturation 40V PNP transistor offers low on state losses making it ideal for use in DC-DC circuits, line switching and particularly charging circuits.



SOT89

FEATURES

- Extremely low equivalent on-resistance
- 5.5 amps continuous current
- Up to 15 amps peak current
- Very low saturation voltages **< -60mV @ -1A**




APPLICATIONS

- **Charging circuits**
- DC - DC converters
- MOSFET gate drivers
- Power switches
- Motor control

ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZX5T3ZTA	7”	12mm	1000 units

PINOUT



TOP VIEW

DEVICE MARKING

- 53Z

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	LIMIT	UNIT
Collector-base voltage	BV_{CBO}	-50	V
Collector-base voltage	BV_{CBS}	-50	V
Collector-emitter voltage	BV_{CEO}	-40	V
Emitter-base voltage	BV_{EBO}	-7.5	V
Continuous collector current [b]	I_C	-5.5	A
Peak pulse current	I_{CM}	-15	A
Power dissipation at T_A =25°C [a]	P_D	0.9	W
Linear derating factor		7.2	mW/°C
Power dissipation at T_A =25°C [b]	P_D	1.5	W
Linear derating factor		12	mW/°C
Power dissipation at T_A =25°C [c]	P_D	2.1	W
Linear derating factor		16.8	mW/°C
Power dissipation at T_A =25°C [d]	P_D	3	W
Linear derating factor		24	mW/°C
Operating and storage temperature range	T_j, T_{stg}	-55 to 150	°C


THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to ambient [a]	$R_{\Theta JA}$	139	°C/W
Junction to ambient [b]	$R_{\Theta JA}$	83	°C/W
Junction to ambient [c]	$R_{\Theta JA}$	60	°C/W
Junction to ambient [d]	$R_{\Theta JA}$	42	°C/W

NOTES

(a) For a device surface mounted on 15mm x 15mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.
(b) For a device surface mounted on 25mm x 25mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.
(c) For a device surface mounted on 50mm x 50mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.
(d) For a device surface mounted on 25mm x 25mm x 1.6mm FR4 PCB measured at t< 5 secs.

CHARACTERISTICS




ZX5T3Z

ELECTRICAL CHARACTERISTICS (at T_{amb} = 25°C unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
Collector-base breakdown voltage	BV_{CBO}	-50	-90		V	I_C=-100μA
Collector-emitter breakdown voltage	BV_{CES}	-50	-90		V	I_C=-100μA
Collector-emitter breakdown voltage	BV_{CEO}	-40	-58		V	I_C=-10mA*
Emitter-base breakdown voltage	BV_{EBO}	-7.5	-8.3		V	I_E=-100μA
Collector cut-off current	I_{CBO}		<1	-20	nA	V_{CB}=-40V
Collector cut-off current	I_{CES}		<1	-20	nA	V_{CB}=-32V
Emitter cut-off current	I_{EBO}		<1	-20	nA	V_{EB}=-6V
Collector-emitter saturation voltage	$V_{CE(SAT)}$		-15	-30	mV	I_C=-0.1A, I_B=-10mA*
			-44	-60	mV	I_C=-1A, I_B=-100mA*
			-50	-70	mV	I_C=-1A, I_B=-50mA*
			-120	-165	mV	I_C=-1A, I_B=-10mA*
			-70	-80	mV	I_C=-2A, I_B=-200mA*
			-125	-175	mV	I_C=-2A, I_B=-40mA*
			-130	-175	mV	I_C=-3.5A, I_B=-175mA*
			-162	-185	mV	I_C=-5.5A, I_B=-550mA*
Base-emitter saturation voltage	$V_{BE(SAT)}$		-820	-900	mV	I_C=-2A, I_B=-40mA*
			-1000	-1075	mV	I_C=-5.5A, I_B=-550mA*
Base-emitter turn-on voltage	$V_{BE(ON)}$		-778	-850	mV	I_C=-2A, V_{CE}=-2V*
			-869	-950	mV	I_C=-5.5A, V_{CE}=-2V*
Static forward current transfer ratio	H_{FE}	200	390			I_C=-10mA, V_{CE}=-2V*
		200	350	550		I_C=-0.5A, V_{CE}=-2V*
		170	290			I_C=-2A, V_{CE}=-2V*
		110	175			I_C=-5.5A, V_{CE}=-2V*
Transition frequency	f_T		152		MHz	I_C=-50mA, V_{CE}=-10V f=100MHz
Output capacitance	C_{OBO}		53		pF	V_{CB}=-10V, f=1MHz*
Switching times	t_d		18		ns	I_C=-1A, V_{CC}=-10V,
	t_r		17			I_{B1}=I_{B2}=-100mA
	t_s		325			
	t_r		60			
Switching times	t_d		55		ns	I_C=-2A, V_{CC}=-30V,
	t_r		107			I_{B1}=I_{B2}=-20mA
	t_s		264			
	t_r		103			


* Measured under pulsed conditions. Pulse width ≤ 300μs; duty cycle ≤2%.

TYPICAL CHARACTERISTICS




ZX5T3Z

PACKAGE OUTLINE



PAD LAYOUT DETAILS



SOT89 pattern.
Minimum Pad Size (dimensions in mm)

Controlling dimensions are in millimeters. Approximate conversions are given in inches

PACKAGE DIMENSIONS

DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min	Max	Min	Max		Min	Max	Min	Max
A	1.40	1.60	0.550	0.630	e	1.40	1.50	0.055	0.059
b	0.38	0.48	0.015	0.019	E	3.75	4.25	0.150	0.167
b1	-	0.53	-	0.021	E1	-	2.60	-	0.102
b2	1.50	1.80	0.060	0.071	G	2.90	3.00	0.114	0.118
c	0.28	0.44	0.011	0.017	H	2.60	2.85	0.102	0.112
D	4.40	4.60	0.173	0.181	-	-	-	-	-

© Zetex plc 2003

Europe

Zetex plc
Fields New Road
Chadderton
Oldham, OL9 8NP
United Kingdom
Telephone (44) 161 622 4444
Fax: (44) 161 622 4446
hq@zetex.com

Zetex GmbH
Streitfeldstraße 19
D-81673 München
Germany
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49
europe.sales@zetex.com

Americas

Zetex Inc
700 Veterans Memorial Hwy
Hauppauge, NY 11788
USA
Telephone: (1) 631 360 2222
Fax: (1) 631 360 8222
usa.sales@zetex.com

Asia Pacific

Zetex (Asia) Ltd
3701-04 Metroplaza Tower 1
Hing Fong Road
Kwai Fong
Hong Kong
Telephone: (852) 26100 611
Fax: (852) 24250 494
asia.sales@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to **www.zetex.com**

ISSUE 1 - OCTOBER 2003