



PC Board Layout  
Component Side Shown

NOTES:

MATERIAL :

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE φ0.46mm.
- 3.PLATING :GOLD PLATING OVER NICKEL.
- 4.SWELD :0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.
- 5.LED :OPTION

ELECTRICAL:

- 1.VOLT TAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC.
- 5.DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50HZ 1MIN.

MECHANICAL:

- 1.DURRABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1.STORAGE :-40V~+85V
- 2.OPERATION :0? TO 70?.

PART NUMBER:

TOLERANCE TABLE

±0.30	±0.05
±0.20	±0.05
±0.00	±0.05

APPROVED:	DATE:	TITLE:
CHECKED:	DATE:	RJ45-8P/8C 1x2 双端插 弯插 短体 带屏蔽 无灯 无弹片
DRAWN:	DATE:	PART. NO. C3026488 (R-RJ45R08P-2003)
SXA	2017-03-18	UNIT mm SCALE free
		FILE NO. Chart-RJ45-0155
		REV. A HY04

深圳市灿科盟实业有限公司  
CHANKLEMENT INDUSTRYCO., LTD