

LF Transmitter Antenna AS737



RoHS



Description

- LF transmitter antenna.
- L × W × H: 74.3 × 14.7 × 7.7 mm Max.
- Product weight: 15.5 g (harness excluded).
- Waterproof level: IPX4.
- Pre-set resonant frequency to 125kHz, 134.2kHz or customization.
- Reference electric field: 99dB μ V/m@3m (@ 125kHz, 1.0App)
- Over molding, with/without connector.
- 2 wires or 3 wires be available for harness.
- RoHS compliance.

Environmental Data

- Operating temperature range: -40°C~+85°C
- Storage temperature range: -40°C~+85°C


Packaging

- Plastic tray and carton box.
- Carton dimension: 500 × 300 × 175mm.
- 100pcs/box.


Applications

- PEPS, Smart key system.
- Security system

Connection




3 wires



2 wires

Dimension - [mm]



LF Transmitter Antenna AS737



Electrical Characteristics

Part No.	Tuning capacitance	Resonant frequency	Resonant Current	Load resistance
AS737-125-332	3.3nF	125±1.0kHz	0.7App	4.7 Ω
AS737-125-682	6.8nF	125±1.0kHz	1.2App	4.7 Ω
AS737-125-103	10nF	125±1.0kHz	1.8App	4.7 Ω
AS737-125-153	15nF	125±1.0kHz	1.8App	4.7 Ω
AS737-125-223	22nF	125±1.0kHz	2.0App	4.7 Ω
AS737-134-332	3.3nF	134.2±1.0kHz	1.1App	4.7 Ω
AS737-134-682	6.8nF	134.2±1.0kHz	1.2App	4.7 Ω
AS737-134-103	10nF	134.2±1.0kHz	1.8App	4.7 Ω
AS737-134-153	15nF	134.2±1.0kHz	1.9App	4.7 Ω
AS737-134-223	22nF	134.2±1.0kHz	2.1App	4.7 Ω

For more information, please browse our website <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6688
FAX.+852-2565-9600

Tokyo

Tel.+81-3-5202-7112
FAX.+81-3-5202-7105

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720

Shanghai

Tel.+86-021-5836-3299
FAX.+86-021-5836-3266

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778

Oberzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338

Singapore

Tel.+65-6296-3388
FAX.+65-6296-3390

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308