

COAXIAL RESONATOR OSCILLATOR

Model 511051

650 MHz

Features

- Low Phase Noise Bipolar Transistor
- Rugged Construction for Extreme Environmental Conditions
- High Frequency Stability
- Voltage Tuning Option

Specifications



CHARACTERISTIC	TYPICAL Ta = 25 °C	MIN/MAX Ta = -10 °C to +60 °C
Frequency	650 MHz	650 MHz
Output Power (dBm)	+10	+13 Max.
Spurious (dBc)	-60	-60
Phase Noise (dB)	-54 dBc/Hz @ 100 Hz -94 dBc/Hz @ 1 KHz -117 dBc/Hz @ 10 KHz -142 dBc/Hz @ 100 KHz -152 dBc/Hz @ 1 MHz	
VSWR	1.5	2.0
Harmonics (dBc)	-20	-20
Frequency Pushing	+/- 0.1% / Volt	+/- .02% / Volt
Frequency Pulling	+/- 0.02%	+/- 0.03%
Temperature Drift	+/- 0.01%	+/- 0.02%
Storage Temperature	-55 °C	+125 °C
Supply Power	DC 15 mA 150	15 155

Spectrum Microwave CROs produce impressive frequency stability and phase noise when used in a properly designed oscillator circuit. The units can be voltage tuned with a varactor over 5% bandwidth and still retain excellent stability and phase noise performance.

Maximum Ratings

Ambient Operating Temperature -55°C to +100 °C
 Storage Temperature -62°C to +125 °C
 Case Temperature +125 °C
 DC Voltage +20 Volts
 Maximum DC Tuning Voltage +20 Volts
 Minimum DC Tuning Voltage 0 Volts

NOTE: Care should always be taken to effectively ground the case of each unit.



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

Rev.
3/6/08

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001