



ZWS15B-5/A

Sales Region	Worldwide	
Series	ZWS-B	
Status	Production	
Feature		
Option	With cover type	
Option Lineup	Please refer to here.	
Recommended EMC Filter	Please refer to here.	
Accessories	Please refer to the catalog	



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 370V	
Efficiency	78% Тур.	
Rated Output Voltage[DC]	5V	
Output Voltage Range[DC]	4.5 to 5.5V	
Maximum Output Current	ЗА	
Maximum Output Power	15W	

Cases Shape & Size		
Case'] shape	PC board	
Width(W)	60mm Nom.	
Height(H)	32mm Nom.	
Depth(D)	107.5mm Nom.	
Weight	125g Typ.	

Other		
Operating Temp. Range	-10 to 60°C	
Cooling	Convection cooling	
	UL60950-1	
Cofety (tordered)(Cortifical)	CSA C22.2 No.60950-1	
Safety Standard(Certified)	EN60950-1	
	EN50178 (OV II)	
Safety Standard(Conformed)	Den-an	
Demonitor	This page only shows representative characteristics. Please refer to the	
Remarks	technical data for detailed specifications and conditions.	

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.