



Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime,  
Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz

## Detectors Technical Data Sheet

PE80T6008

The PE80T6008 is a coaxial packaged Tunnel Diode Detector that features rugged Germanium (Ge) planar construction and operates over a broadband frequency range of 6.0 to 18.0 GHz. The zero biased design features extremely low video output resistance of 125 ohms typical, and an extremely fast pulse response risetime of 5 nsec typical. Additional desirable features include excellent dynamic range with very efficient low level RF signal detection, wide video bandwidth, and excellent loaded voltage output sensitivity. The Detector exhibits an extremely stable and flat Negative Output Polarity response across a wide frequency band and has excellent temperature stability across an operating temperature range of -65°C to +115°C. Maximum CW input power handling is +17 dBm. The compact cylindrical package features an SMA male RF input connector and an SMA female Video output connector.

### Features

- Tunnel Diode Detector
- Rugged Germanium (Ge) Planar Construction
- Broadband Frequency: 0.1 to 2 GHz
- Zero Bias Design
- Negative Video Output
- Operational Temperature: -65°C to +115°C
- Extremely Fast Pulse Video Response: 5 nsec typ. risetime
- Max CW Input Power +17 dBm
- Extremely Low Video Resistance: 125 ohms typical
- SMA Male RF Input and SMA Female Video Output Connectors
- Excellent Temperature Stability
- Excellent Dynamic Range with Very Efficient Low Level Signal Detection
- Excellent Loaded Voltage Output Sensitivity

### Applications

- Transmitter Monitoring
- Radar Equipment
- Missile Guidance Systems
- Input to Low Noise Amplifiers
- ECM Receivers
- Power and Signal Monitors
- Doppler Radar and Beacon Receivers
- Test & Measurement
- Pulse Applications

### Electrical Specifications

| Description                         | Minimum | Typical | Maximum | Units |
|-------------------------------------|---------|---------|---------|-------|
| Frequency Range                     | 6 GHz   |         | 18 GHz  |       |
| VSWR                                |         | 3:1     |         |       |
| Pulse Video Response Risetime       |         | 5       |         | ns    |
| Voltage Sensitivity                 |         | 700     |         | mV/mW |
| Flatness                            |         |         | ±0.75   | dB    |
| Input Power                         |         |         | +17     | dBm   |
| Video Output Resistance             |         | 125     |         | Ohms  |
| Video Capacitance                   |         | 10      |         | pF    |
| Tangential Signal Sensitivity (TSS) |         | -47     |         | dBm   |
| Operating Temperature Range         | -65     |         | +115    | deg C |

#### Electrical Specification Notes:

Typical values are measured at +25°C and are not guaranteed. TSS is measured with a 2 MHz video bandwidth and 2 dB NF amplifier. Input Power is 17 dBm or 3 ERG Spike Max

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime, Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz PE80T6008](#)



Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime,  
Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz

## Detectors Technical Data Sheet

PE80T6008

### Mechanical Specifications

**Size**

|        |                    |
|--------|--------------------|
| Length | 1.21 in [30.73 mm] |
| Width  | 0.81 in [20.57 mm] |

### Environmental Specifications

**Temperature**

|                 |                   |
|-----------------|-------------------|
| Operating Range | -65 to +115 deg C |
| Storage Range   | -65 to +125 deg C |

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime, Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz PE80T6008](#)





Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime,  
Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz

Detectors Technical Data Sheet

PE80T6008

**Typical Performance Data**

Typical Performance at +25° C



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime, Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz PE80T6008](#)



Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime,  
Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz

## Detectors Technical Data Sheet

PE80T6008

Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime, Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime, Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz PE80T6008](https://www.pasternack.com/tunnel-diode-detector-sma-negative-6-18-ghz-pe80t6008-p.aspx)



URL: <https://www.pasternack.com/tunnel-diode-detector-sma-negative-6-18-ghz-pe80t6008-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

# PE80T6008 CAD Drawing

Tunnel Diode Detector, SMA, 5 nsec Pulse Risetime, Negative Video Out, +17 dBm max Pin, 6 GHz to 18 GHz

| REVISIONS |                 |          |          |
|-----------|-----------------|----------|----------|
| REV.      | DESCRIPTION     | DATE     | APPROVED |
| A         | INITIAL RELEASE | 01/14/19 | T.GALLA  |



**LABEL:**

**PASTERNAK**

J1 PE80T6008 J2

S/N: XXXXX

UNLESS OTHERWISE SPECIFIED  
LEADING DIMENSIONS ARE INCHES  
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:

|           |        |             |
|-----------|--------|-------------|
| X±.2      | [5.08] | FRACTIONS   |
| .XX±.01   | [.25]  | ±.132       |
| .XXX±.005 | [.13]  | ANGLES ± 1° |

ALL DIMENSIONS SHOWN  
ARE FOR REFERENCE ONLY.

THIRD-ANGLE PROJECTION

**(PE) PASTERNAK**  
an INFINITO brand

Pasternack Enterprises, Inc.  
P.O. Box 16759, Irvine, CA 92623.  
Phone: 1.949.261.1920 | 1.866.727.8376  
Fax: 1.949.261.7451  
www.pasternack.com | e-mail: sales@pasternack.com

THE INFORMATION AND  
DESIGN IN THIS DOCUMENT  
IS THE PROPERTY OF  
PASTERNAK CORPORATION.  
ALL RIGHTS RESERVED.

SHEET 1 OF 1  
SCALE N/A

SIZE A CAGE 53919 DRAWN BY KDANG PART NUMBER PE80T6008 REV A

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.