


GSP150-102-3P400



Sales Region	Worldwide (except Japan)
Series	GENESYS+
Model	G+3U 15kW
Status	 Production
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics

Input	3-phase
Input Voltage Range[AC]	342 to 460Vac
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	150Vdc
Output Voltage[DC]	0 to 150Vdc
Rated Output Current	102A
Output Current	0 to 102A
Rated Output Power	15.3kW
Efficiency	91% Typ.
Voltage Ripple Noise	0.02Vrms (5Hz to 1MHz)
Current Ripple Noise	0.023Arms (5Hz to 1MHz)

Package Type & Size

Package Type	3U Rack mount / Bench top
Width(W)	423mm Nom. (16.65in Nom.)
Height(H)	132.5mm Nom. (5.22in Nom.)
Depth(D)	441.5mm Nom. (17.38in Nom.)
Weight	23.5kg Typ. (51.8lbs Typ.)

Other

Interfaces Included	LAN (LXI compliant)
	USB
	RS-232
	RS-485
Interface Options	Isolated analog voltage control
	GPIB
	EtherCAT
Operating Temp. Range	Modbus-TCP
	0 to 50°C

Safety Standard(Certified)	IEC60950-1 UL60950-1 CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.