

Han 70A Hybrid module, female 6-16mm²



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 14 005 2741 |
| Specification | Han 70A Hybrid module, female 6-16mm ² |
| HARTING eCatalogue | https://b2b.harting.com/09140052741 |

Identification

| | |
|----------------|-------------------------------------|
| Category | Modules |
| Series | Han-Modular [®] |
| Type of module | Han [®] 70 A Hybrid module |

Version

| | |
|--------------------|---|
| Termination method | Axial screw termination / crimp termination |
| Gender | Female |
| Number of contacts | 1 |
| further contacts | + 4 additional signal contacts |
| Details | Please order signal contacts separately. |

Technical characteristics

| | |
|--------------------------------|--------------------------|
| Conductor cross-section | 6 ... 16 mm ² |
| Rated current | 70 A |
| Rated voltage | 1,000 V |
| Rated impulse voltage | 8 kV |
| Pollution degree | 3 |
| Rated current (signal) | 16 A |
| Rated voltage (signal) | 400 V |
| Rated impulse voltage (signal) | 6 kV |
| Pollution degree (signal) | 3 |
| Insulation resistance | >10 ¹⁰ Ω |
| Contact resistance | ≤0.5 mΩ |



Pushing Performance

Technical characteristics

| | |
|----------------------|---------------------------|
| Stripping length | 11 ... 12 mm |
| Tightening torque | 2 Nm @ 6 mm ² |
| | 3 Nm @ 10 mm ² |
| | 4 Nm @ 14 mm ² |
| | 4 Nm @ 16 mm ² |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | ≥500 |

Material properties

| | |
|---|---|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 5dbb3851-b94e-4e88-97a1-571845975242 |

Specifications and approvals

| | |
|----------------|-----------------------|
| Specifications | EN 60664-1 |
| | IEC 61984 |
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 |

Commercial data

| | |
|--------------------------------|----------|
| Packaging size | 2 |
| Net weight | 20.9 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |



Pushing Performance

Commercial data

eCl@ss

27440217 Module for industrial connectors (power/signals)