



MARK: KINGS M39012/20-0006 756-21-7
YRMK (DATE CODE)

NOTES:

1. FOR USE WITH RG-58, 58A, 58C, 141, 141A & 303/U CABLE.
 2. FOR CABLING INSTRUCTIONS SEE CP-465.
 3. FOR CRIMPING USE DIE KTH-2001.
 4. INTERFACE PER MIL-STD-348, FIG. 301-1.
 5. CONTACT MUST BE SOLDERED ON RG-58/U BUT MAY BE CRIMPED ON BALANCE OF CABLE GROUPS.
- 6. MATERIALS:**
 INSULATORS: TEFLON, ASTM-D1457
 GASKET: SIL. RUB., PER A-A-59588
 K-GRIP SLEEVE: COM. BRONZE; ASTM-B-135
 ANGLE CONTACT } BER. COP., ASTM-B-196
 OUTER CONTACT }
 ALL OTHER PARTS: BRASS, ASTM-B16
- 7. FINISHES:**
 CENTER CONTACTS: HARD GOLD P.L.T. PER ASTM-B488
 ALL OTHER METAL PARTS: SILVER PLATE PER ASTM-B700
- 8. ELECTRICAL CHARACTERISTICS:**
 NOMINAL IMPEDANCE: 50 OHMS
 FREQUENCY RANGE: DC TO 4 GHz.
 VOLTAGE RATING: 500 VRMS

PART NO. 756-21-7

REVISIONS	
ISSUE	CHANGES
C	ER 23675 JUN 04/27/10

CUSTOMER
SALES DRAWING

SCALE 4:1

APPROX SURFACE AREA

WAS E-20175, REPLACES KC-59-352.

USED ON

REF: 756-19-7

PLUG, ANG, BNC

M39012/20-0006

DRAWN	HWN	DATE	03/14/03
DESIGN	HWN	DATE	03/14/03
APPR.		DATE	

KINGS
 Winchester Electronics
 62 Service Industrial
 Road North
 Winchester, MA 01890

SD756-21-7