PASTERNACK
THE ENGINEER'S RF SOURCE



Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL

Electromechanical Relay Switches Technical Data Sheet PE71S6204

Features

- Transfer Switch
- DC to 12.4 GHz Operating Frequency Range
- 1 M Cycles min
- Failsafe Switch
- Indicator
- TTL Contol
- Switching Sequence Break Before Make

Applications

- Test & Measurement
- Communications System
- Instrumentation

Description

The PE71S6204 is a Transfer Switch that operates from DC to 12.4 GHz. The switch has a Failsafe actuator and an indicator and 1M life cycles. The switch has an opating voltage of 12 Volts and has TTL control.

Electrical Specifications

Switch Type	Transfer
Actuator Type	Failsafe
Switching Sequence	Break Before Make
Actuator Options	Indicators, TTL Logic
TTL Control	on: “High” 2.4 to 5 Volts off: “Low” 0 to 0.8 Volts

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
Impedance		50		Ohms
Operating Voltage		12		Volts
Actuating Current @ 12 Volts		540		mA
VSWR			1.7:1	
Insertion Loss			0.6	dB
Isolation	60			dB
Input Power (CW) (@ 12.4 GHz)			50	Watts

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL PE71S6204

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2015 Pasternack Enterprises All Rights Reserved

PASTERNACK
THE ENGINEER'S RF SOURCE



Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL

Electromechanical Relay Switches Technical Data PE71S6204

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 4	4 to 8	8 to 12.4			GHz
VSWR, Max	1.2:1	1.6:1	1.7:1			
Insertion Loss, Max	0.2	0.5	0.6			dB
Isolation, Min	80	65	60			dB

Mechanical Specifications

Size

Length	2 in [50.8 mm]
Width/Diameter	2 in [50.8 mm]
Height	2.06 in [52.32 mm]
Weight	0.875 lbs [396.89 g]
Body Material and Plating	Aluminum, Gold
Operating Life	1,000,000 Cycles
Switching Time	50 ms Max

Connectors

RF Connector Type	TNC Female
RF Connector Contact Material and Plating	Beryllium Copper, Gold
RF Connector Body Plating	Passivated Stainless Steel

Environmental Specifications

Temperature

Operating Range	-25 to +65 deg C

Compliance Certifications (visit www.Pasternack.com for current document)

Not RoHS Compliant

Plotted and Other Data

Notes:

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL PE71S6204

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered


© 2015 Pasternack Enterprises All Rights Reserved




Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL

Electromechanical Relay Switches Technical Data PE71S6204

Typical Performance Data





Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL PE71S6204

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2015 Pasternack Enterprises All Rights Reserved

PASTERNACK®
THE ENGINEER'S RF SOURCE



Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL

Electromechanical Relay Switches Technical Data PE71S6204

Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Transfer Electromechanical Relay Switch DC to 12.4 GHz, TNC, 50 Watts, 12V Control with Indicators, TTL PE71S6204

URL: http://www.pasternack.com/tnc-transfer-electromechanical-relay-switch-12.4-ghz-indicators-ttl-logic-pe71s6204-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.


Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2015 Pasternack Enterprises All Rights Reserved

PE71S6204 CAD Drawing

Transfer Electromechanical Relay Switch DC to 12.4 GHz,
TNC, 50 Watts, 12V Control with Indicators, TTL



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE: DECIMALS .XX ± .03 (0.76) .XXX ± .010 (0.254) ANGLES ±1° FRACTIONS ±1/16	
HOLE DIAMETER .0135 TO .125 (0.343 TO 3.175)	TOLERANCE +.004 TO –.001 (+0.102 TO –0.025)
.126 TO .250 (3.200 TO 6.350)	+.005 TO –.001 (+0.127 TO –0.025)
.251 TO .500 (6.375 TO 12.700)	+.006 TO –.001 (+0.152 TO –0.025)
.501 TO .750 (12.725 TO 19.050)	+.008 TO –.001 (+0.203 TO –0.025)
.751 TO 1.000 (19.075 TO 25.400)	+.010 TO –.001 (+0.254 TO –0.025)
1.001 TO 2.000 (25.425 TO 50.800)	+.012 TO –.001 (+0.305 TO –0.025)

* THESE DIMENSIONS AND TOLERANCES SUPERSEDE NOTE #1 ON TITLE BLOCK.

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE **PE71S6204**

CAD FILE 091515 | SCALE N/A | SIZE A | 2233


FSCM NO. 53919

PASTERNACK® THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

© 2015 Pasternack Enterprises All Rights Reserved

PE71S6204 CAD Drawing

Transfer Electromechanical Relay Switch DC to 12.4 GHz,
TNC, 50 Watts, 12V Control with Indicators, TTL



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE	091515	SCALE N/A	SIZE A	2233

DWG TITLE **PE71S6204**

FSCM NO. 53919

PASTERNACK® THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

© 2015 Pasternack Enterprises All Rights Reserved