

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
FT	0		S2	REVISED PER ECO-11-004917	11MAR11	RK	HMR

D

C

B

A

MOUNTING TAB
2 PLC
SEE TABLE

2.64±0.10 DIA
[.104±.004]
2 HOLES

4.98
[.196]
TYP

17.37
[.684]
22.61 MAX
[.890]

12.70
[.500]

18.16 MAX
[.715]

HOUSING

CONTACT
TYP

MATING FACE

12.70
[.500]

4.60±0.64
[.181±.025]
TYP

0.99 DIA
[.039]
TYP

2.54
[.100]
2 PLC

11.79
[.464]

2.64±0.05 DIA
[.104±.002]
2 HOLES

1.60±0.05 DIA
[.063±.002]
4 HOLES

4.98
[.196]

6.20
[.244]

2.49
[.098]

RECOMMENDED PC BOARD LAYOUT

- 1

NYLON, UL 94V-0 RATED, RED.
- 2

BRASS PER ASTM B36.
- 3

3.81um [.000150] MIN TIN OVER 2.54um [.000100] MIN COPPER.
- 4

0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] FROM MATING END, 3.81um [.000150] MIN TIN FOR A LENGTH OF 4.83 [.190] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.
- 5

CONTACTS SELECT LOADED IN POSITIONS 2, 3 AND 4.
- 6

3.81um [.000150] MIN TIN OVER 2.54um [.000100] MIN COPPER.
- 7

0.76um [.000030] MIN GOLD FOR A LENGTH OF 5.08 [.200] FROM MATING END, 3.81um [.000150] MIN TIN FOR A LENGTH OF 4.83 [.190] MIN FROM OPPOSITE END, BOTH OVER 1.27um [.000050] MIN NICKEL.
- 8

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8 5 OBSOLETE	6	YES	1-207119-2
	7	NO	1-207119-1
	7	YES	1-207119-0
	6	NO	207119-9
8 5 OBSOLETE	6	YES	207119-8
	3	YES	207119-7
	4	NO	207119-4
	4	YES	207119-3
	3	NO	207119-2
	3	YES	207119-1
CONTACT FINISH		MOUNTING TABS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L.SIPE 03/10/92		 TE Connectivity							
		CHK R.STONE 3-17-92									
DIMENSIONS: mm [INCHES]		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		NAME PIN HEADER ASSEMBLY, 4 POSITION, METRIMATE							
		APVD —									
		PRODUCT SPEC 108-10033									
		APPLICATION SPEC									
		—									
MATERIAL		FINISH		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO				
HOUSING: 1		CONTACT: SEE TABLE		WEIGHT —	A2	00779	C=207119	—			
CUSTOMER DRAWING						SCALE	4:1	SHEET	1 of 1	REV	S2