


Front Bend

SPECIFICATIONS:

- Current rating:4A AC,DC
- Voltage rating:250V AC,DC
- Temperature range:-40°C~+130°C
- Contact resistance:3.0mVMax.
- Insulation resistance:5000MVMIn.
- Withstanding Voltage:2200V AC/minute
- UL File No:E304945
- Contact:0.64mm squareX18.00mm Length
- Material:HSG:Nylon66 UL94V-0
TER:Brass, Tin plated
- HSG and PIN solid needle bearing:2.0kg(min)
- Solder Resistance:Dip connector terminal tails in solder :Solder duration:4±0.5 Seconds; Solder temperature:245°C±0.5°C
- Part NO:M2545R-N-K (A)



Part NO	A	B	Part NO	A	B
2	5.08	2.54	10	25.40	22.86
3	7.62	5.08	11	27.94	25.40
4	10.16	7.62	12	30.48	27.94
5	12.70	10.16	13	33.02	30.48
6	15.24	12.70	14	35.56	33.02
7	17.78	15.24	15	38.10	35.56
8	20.32	17.78	16	40.64	38.10
9	22.86	20.32			

Part name (零件名称)	Edition (版本)	Date (日期)	 THIRD ANGLE PROJECTION
M2545R-N-K(A)	B	2010.05.13	
drawing number (图号)			UNIT:mm
CRS012-02			Tolerance: .000 ±0.10 .00 ±0.20 .0 ±0.30

东莞市兴飞连接器有限公司

Drawing (制图)
吕叔锋

Confirmation (审核)