
ROITHNER LASERTECHNIK GmbH
WIEDNER HAUPTSTRASSE 76 1040 VIENNA AUSTRIA
TEL. +43 1 586 52 43 -0, FAX. -44, OFFICE@ROITHNER-LASER.COM

LED22



TECHNICAL DATA


Mid-Infrared Light Emitting Diode


Light Emitting Diodes with central wavelength 2.25 µm series are based on heterostructures grown on GaSb substrates. They are developed for using in optical gas sensors and medical diagnostics. LED22 has a stable ouput power and a lifetime more then 80000 hours.



Features

- Structure: GaInAsSb/AlGaAsSb
- Peak Wavelength: typ. 2.25 µm
- Optical Ouput Power: typ. 1.1 mW qCW
- Package: TO-18, with cap and without window






(Unit: mm)

Specifications

Item	Condition	Rating			Unit
		Min.	Typ.	Max.	
Peak Wavelength	T=300 K	2.20	2.25	2.29	µm
FWHM	150 mA CW	150	200	250	nm
Quasi-CW Optical Power	200 mA qCW	0.9	1.1	1.3	mW
Pulsed Optical Power	1 A	25	28	30	mW
Switching Time	T=300 K	10	30	50	ns
Operation Voltage	200 mA qCW				V
Operating Temperature	-240 … +50				°C
Emitting Area	300x300				µm
Soldering Temperature	180				°C
Package	TO-18, with non-removeable cap and without window				

Operating Regime



Quasi-CW

- Maximum current 220 mA
- Recommended current 150-200mA

Pulsed

- Maximum current 1 A
  (puls lenght 500 ns, repetition rate 2kHz)

ROITHNER LASERTECHNIK GmbH
WIEDNER HAUPTSTRASSE 76 1040 VIENNA AUSTRIA
TEL. +43 1 586 52 43 -0, FAX. -44, OFFICE@ROITHNER-LASER.COM

Typical Performance Curves

