



Price* : 4,671.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	J

Complementary

Line Rated Current	225 A
Number of poles	2
Poles description	2P
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC
[Ue] rated operational voltage	600 V AC 250 V DC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Terminal nut line
AWG gauge	AWG 3/0...350 kcmil aluminium/copper
Magnetic hold current	1125 A
Magnetic tripping current	2250 A
Height	7.52 in (191.01 mm)
Maximum Width	4.12 in (104.65 mm)
Maximum Depth	5 in (127.00 mm)
Tightening torque	230.12 lbf.in (26 N.m) 0.15...0.29 in ² (95...185 mm ²) AWG 3/0...350 kcmil)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product certifications	IEC CSA UL Listed CCC CE
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01115-HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
Package weight(Lbs)	3.70 lb(US) (1.678 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------