9.2x8x1.92mm Commercial 1 Power Warm White LED
OSM5XAC1C1E


▪Features

- Highest luminous flux
- Super energy efficiency
- Very long operating life (up to 100K hours)
- Superior ESD protection
- No UV

▪Applications

- Read lights (car, bus, aircraft)
- Portable (flashlight, bicycle)
- Bollards / Security / Garden
- Traffic signaling / Beacons
- In door / Out door Commercial lights
- Automotive Ext

▪Outline Dimension




Unite:mm
Tolerance:± 0.30

▪Absolute Maximum Rating (Ta=25℃)

Item	Symbol	Value	Unit
DC Forward Current	I_F	400	mA
Pulse Forward Current*	I_{FP}	500	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	1600	mW
Operating Temperature	Topr	-30 ~ +85	℃
Storage Temperature	Tstg	-40~ +100	℃
Lead Soldering Temperature	Tsol	260℃/5sec	-

*Pulse width Max.10ms Duty ratio max 1/10


▪Directivity



■Electrical -Optical Characteristics (Ta=25℃)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
DC Forward Voltage	V_F	I_F=350mA	3.0	3.3	4.0	V
DC Reverse Current	I_R	V_R=5V	-	-	10	μA
Luminous Flux	Flux	I_F=350mA		50	70	lm
Color Temperature	CCT	I_F=350mA	-	3000	-	K
Chromaticity Coordinate*	x	I_F=350mA	-	0.45	-	
	y	I_F=350mA	-	0.41	-	
50% Power Angle	$2\theta_{1/2}$	I_F=350mA	-	120	-	deg

■Forward Operating Current (DC)



Note: Don't drive at rated current more than 5s without heat sink for Commercial 1 Power emitter series.