

HFE2500-48/S



<b>Sales Region</b>	Worldwide
<b>Series</b>	HFE
<b>Status</b>	Production
<b>Feature</b>	
<b>Option</b>	PM Bus option
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	
Efficiency	92% Typ.
Rated Output Voltage[DC]	48V
Output Voltage Range[DC]	38.4 to 58V
Maximum Output Current	52A
Maximum Output Power	2496W

### Cases Shape & Size

Case shape	Unit
Width(W)	107mm Nom.
Height(H)	41mm Nom.
Depth(D)	325mm Nom.
Weight	2100g Typ.

### Other

Operating Temp. Range	-10 to 70°C
Cooling	Blower fan cooling
Safety Standard(Certified)	UL60950-1 EN60950-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.