3.0A SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER Reverse Voltage - 100 to 1000 V

Forward Current – 3.0A


lead-free ROHS

FEATURES

- Fast reverse recovery time
- Designed for Surface Mount Application
- Glass Passivated Chip Junction
- Low power loss, high efficiency
- Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

- Case: UMSB
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.234g / 0.00825oz



1.Input pin(-)
2.Input pin(+)
3.Output Anode(~)
4.Output Cathode(~)

UMSB

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	UMSB30B	UMSB30D	UMSB30G	UMSB30J	UMSB30K	UMSB30M	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	100	200	400	600	800	1000	V
Average Rectified Output Current at T_c = 125 °C	I_o	3.0						A
Peak Forward Surge Current 8.3 ms Single Half Sine-Wave Superimposed on Rated Load(JEDEC method)	I_{FSM}	80						A
Forward Voltage per element at 3.0A	V_F	1.0		1.4	1.6			V
Maximum DC Reverse Current @T_A=25°C at Rated DC Blocking Voltage @T_A=125°C	I_R	5.0 100						μA
Typical Junction Capacitance (Note1)	C_j	50						pF
Maximum Reverse Recovery Time (Note2)	T_{RR}	50			75			nS
Typical Thermal Resistance (Note3)	$R_{\theta JA}$	40						°C/W
Operating and Storage Temperature Range	Tj, Tstg	-55 ~ +150						°C

(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(2) Mounted on glass epoxy PC board with 4×1.5"×1.5" (3.81×3.81 cm) copper pad.

Download from alldatasheet.com

Fig.1 Average Rectified Output Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Instaneous Forward Characteristics




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Repetitive Peak Forward Surage Current



Download from alldatasheet.com


Package Outline UMSB

Plastic surface mounted package; 4 leads



UNIT		A	C	D	E	E_1	L	e	b	∠
mm	max	1.5	0.29	7.0	7.6	8.9	1.6	5.3	1.15	10°
	min	1.3	0.17	6.2	7.1	8.4	1.0	4.9	0.95	
mil	max	59	12	276	299	350	55	209	45	
	min	51	7	244	280	331	31.5	193	37	

The recommended mounting pad size



Unit: mm (mil)

Summary of Packing Options

Package	Packing Description	Packing Quantity	Industry Standard
UMSB	Tape/Reel,13"reel	3000	EIA-481-1

Download from alldatasheet.com