
PNP Silicon AF Transistors



- For general AF applications
- High current gain
- Low collector-emitter saturation voltage
- Complementary types: BCW66... (NPN)
- Pb-free (RoHS compliant) package [1)]
- Qualified according AEC Q101

Type	Marking	Pin Configuration			Package
BCW67A	DAs	1=B	2=E	3=C	SOT23
BCW67B	DBs	1=B	2=E	3=C	SOT23
BCW67C	DCs	1=B	2=E	3=C	SOT23
BCW68F	DFs	1=B	2=E	3=C	SOT23
BCW68G	DGs	1=B	2=E	3=C	SOT23
BCW68H	DHs	1=B	2=E	3=C	SOT23

[1]Pb-containing package may be available upon special request

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	V_{CEO}		V
BCW67		32	
BCW68		45	
Collector-base voltage	V_{CBO}		
BCW67		45	
BCW68		60	
Emitter-base voltage	V_{EBO}	5	
Collector current	I_C	800	mA
Peak collector current	I_{CM}	1	A
Base current	I_B	100	mA
Peak base current	I_{BM}	200	
Total power dissipation, $T_S \leq 79°C$	P_{tot}	330	mW
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-65 ... 150	

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point[1)]	R_{thJS}	≤ 215	K/W

[1]For calculation of R_{thJA} please refer to Application Note Thermal Resistance

Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Collector-emitter breakdown voltage	$V_{(BR)CEO}$				V
I_C = 10 mA, I_B = 0 , BCW67		32	-	-	
I_C = 10 mA, I_B = 0 , BCW68		45	-	-	
Collector-base breakdown voltage	$V_{(BR)CBO}$				
I_C = 10 µA, I_E = 0 , BCW67		45	-	-	
I_C = 10 µA, I_E = 0 , BCW68		60	-	-	
Emitter-base breakdown voltage	$V_{(BR)EBO}$	5	-	-	
I_E = 10 µA, I_C = 0					
Collector-base cutoff current	I_{CBO}				µA
V_{CB} = 32 V, I_E = 0		-	-	0.02	
V_{CB} = 45 V, I_E = 0		-	-	0.02	
V_{CB} = 32 V, I_E = 0 , T_A = 150 °C; BCW67		-	-	20	
V_{CB} = 45 V, I_E = 0 , T_A = 150 °C; BCW68		-	-	20	
Emitter-base cutoff current	I_{EBO}	-	-	20	nA
V_{EB} = 4 V, I_C = 0					
DC current gain[1)]	h_{FE}				-
I_C = 100 µA, V_{CE} = 10 V, h_{FE}-grp.A/F		35	-	-	
I_C = 100 µA, V_{CE} = 10 V, h_{FE}-grp.B/G		50	-	-	
I_C = 100 µA, V_{CE} = 10 V, h_{FE}-grp.C/H		80	-	-	
I_C = 10 mA, V_{CE} = 1 V, h_{FE}-grp.A/F		75	-	-	
I_C = 10 mA, V_{CE} = 1 V, h_{FE}-grp.B/G		120	-	-	
I_C = 10 mA, V_{CE} = 1 V, h_{FE}-grp.C/H		180	-	-	
I_C = 100 mA, V_{CE} = 1 V, h_{FE}-grp.A/F		100	160	250	
I_C = 100 mA, V_{CE} = 1 V, h_{FE}-grp.B/G		160	250	400	
I_C = 100 mA, V_{CE} = 1 V, h_{FE}-grp.C/H		250	350	630	
I_C = 500 mA, V_{CE} = 2 V, h_{FE}-grp.A/F		35	-	-	
I_C = 500 mA, V_{CE} = 2 V, h_{FE}-grp.B/G		60	-	-	
I_C = 500 mA, V_{CE} = 2 V, h_{FE}-grp.C/H		100	-	-	


DC Electrical Characteristics

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Characteristics					
Collector-emitter saturation voltage[1)]	V_{CEsat}				V
I_C = 100 mA, I_B = 10 mA		-	-	0.3	
I_C = 500 mA, I_B = 50 mA		-	-	0.7	
Base emitter saturation voltage[1)]	V_{BEsat}				
I_C = 100 mA, I_B = 10 mA		-	-	1.25	
I_C = 500 mA, I_B = 50 mA		-	-	2	
AC Characteristics					
Transition frequency I_C = 50 mA, V_{CE} = 5 V, f = 20 MHz	f_T	-	200	-	MHz
Collector-base capacitance V_{CB} = 10 V, f = 1 MHz	C_{cb}	-	6	-	pF
Emitter-base capacitance V_{EB} = 0.5 V, f = 1 MHz	C_{eb}	-	60	-	

[1]Pulse test: t < 300µs; D < 2%


DC current gain $h_{FE} = f(I_C)$

V_{CE} = 1 V




Collector-emitter saturation voltage

$I_C = f(V_{CEsat})$, h_{FE} = 10




Base-emitter saturation voltage

$I_C = f(V_{BEsat})$, h_{FE} = 10




Collector cutoff current $I_{CBO} = f(T_A)$

V_{CBO} = 25 V




Transition frequency $f_T = f(I_C)$

V_{CE} = 5 V




Collector-base capacitance $C_{cb} = f(V_{CB})$

Emitter-base capacitance $C_{eb} = f(V_{EB})$




Total power dissipation $P_{tot} = f(T_S)$




Permissible Pulse Load

$P_{totmax}/P_{totDC} = f(t_p)$




Package Outline




1) Lead width can be 0.6 max. in dambar area

Foot Print




Marking Layout (Example)



Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel



Edition 2006-02-01
Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2007.
All Rights Reserved.

Attention please!

The information given in this dokument shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.
Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.
Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.