High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#:

ATS-55250R-C1-R0

Description:

High Performance X-CUT - Heat Sink, T412, BLACK-ANODIZED

Heat Sink Type: Cross-Cut Heat Sink Attachment: Equivalent Part Number: ATS-55250R-C2-R0

THERMAL TAPE

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency cross-cut fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Designed specifically for BGAs and other surface mount packages
- Comes pre-assembled with high performance thermal interface material ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	6.19 °C/W	5.33 °C/W	4.66 °C/W	4.21 °C/W	3.87 °C/W	3.62 °C/W	3.41 °C/W
	Ducted Flow	n/a						

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	25.0 mm	25.0 mm	19.5 mm	mm	T412	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension ATS-5525 (Saint Go Thermal p applicatio ATS resent performant ATS certition 	bain C675). performance data ar n. rves the right to upc	height from the botto cact heat sink assent e provided for refere ate or change its pro- nk assembly is RoH	nbly with an equivale ence only. Actual pe oducts without notic S-6 and REACH co	ent therman rformanc e to impr	al interface material e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA