General Cable Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: E3004S | Revision Level: 4 | Date: 9/26/2008

4C 22 7/30 BC FLEX FLEX — **Sound, Alarm & Security Cable**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#22 AWG 7/30 Bare Copper	0.029” nom.
Insulation:	0.008” Wall FLEXGUARD*	0.045” nom.
Cable:	4C @ 4.5" LHL	0.109” nom.
Jacket:	0.015” Wall FLEXGUARD* - Natural	0.139" +/- 0.007"
Print Legend:	***CAROL A (R) 22 AWG - - E3004S - - 75C E60233-8 60C (UL) CL3P --- C (UL) CMP - - MADE IN USA (DATE CODE & SEQUENTIAL FOOTAGE 1000’ TO 0’)***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3P
National Electrical Code	Article 800
UL Standard 444	Type CMP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	75C
SUGGESTED WORKING VOLTAGE (Vrms):	300V
CONDUCTOR D.C. RESISTANCE:	14.8 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	29.88 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	68 Ohms @ 1MHz nom

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	Red
3	White
4	Green

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

**FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.*