



Screw Connectors

230/ 1 GW

Terminal Block, 1 pole, Insulating Material: PA 6-GW, Cross-Section: 2.5 mm², Pin Spacing: 8.0 mm, Fixing: Screw, Voltage Rating: 450 V, Current Rating: 24 A



Order Info

Reference Number (ref. no.)	1212G1
Applications	Lighting, Installation, Electrical Appliances
PU	0

Type

Type	Terminal Block
Number of poles	1 pole
Clamping Units per Pole	1
Colour	white
Cross-Section	2.5 mm ²
Connection Type	Screw

Technical Data

Voltage Rating	450 V
Current Rating	24 A
Insulating Material	PA 6-GW
Contact Material	Brass
Core Cross-Section min.	0.5 mm ²
Core Cross-Section max.	4.0 mm ²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	5.0-5.5 mm
Assembly Contact Screw	0.8x4.0 / ⌀ 0.5 Nm
Pin Spacing	8.0 mm
Fixing	Screw
Approbation EN60998	200_230_EN60998_20012012_VDE_ENEC_40034813_web.pdf
Approbation UL	230_19820924_20120103_UL_E63492_1-02_Description_web.pdf
Approbation CSA	Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765

Accessories

ZEL 110

196420
