Applied Motion Products, Inc. 404 Westridge Dr. Watsonville, CA 95076, USA 1-800-525-1609 Tel (831) 761-6555 Fax (831) 761-6544

Product Datasheet

www.Applied-Motion.com

4023-998

NEMA 23 Step Motor

1pc. - 50.00 50pc. - 50.00



Product Features

- Closeout sale in progress (single shaft version only)
- Limited quantity in stock
- 2-phase hybrid step motor
- Standard NEMA 23 dimensions
- 1.8 degree step angle



Description

Product Description:

The 4023-998 stepper motor with single shaft (see Note below) is a two-phase hybrid step motor with a NEMA 23 frame size. The motor is no longer in production (and normally listed as archived on our website) but is being offered in a closeout sale to clear our inventory. Once the remaining inventory of this motor is depleted the motor will revert to being listed as archived on our website and will no longer be available for purchase. This makes the motor a good choice for one-time applications, research & development work, and hobbyist projects.

Note: Only the single-shaft version of this motor is available for purchase in the closeout sale. The double-shaft version, 4023-998D, is not available. All sales are final.

Specifications

Part Number:	4023-998
Frame Size:	NEMA 23
Motor Type:	Standard torque
Motor Length:	2.00 inches
Number of Lead Wires:	6
Lead Wire Configuration:	flying leads, no connector
Lead Wire/Cable Length:	18 inches
Lead Wire Gauge:	22 AWG
Unipolar Holding Torque:	53.0 oz-in
Bipolar Holding Torque:	75.0 oz-in
Step Angle:	1.8 deg
Bipolar Series Current:	0.21 A/phase
Bipolar Series Resistance:	160 Ohms/phase
Bipolar Series Inductance:	328 mH/phase
Unipolar Current:	0.30 A/phase
Unipolar Resistance:	80.0 Ohms/phase
Unipolar Inductance:	82.0 mH/phase
Rotor Inertia:	1.56E-03 oz-in-sec ²
Integral Gearhead:	No
Weight:	1.3 lbs
Storage Temperature:	-40 to 70 °C
Operating Temperature:	-20 to 50 °C
Insulation Class:	Class B (130 °C)
Maximum Radial Load:	15 lbs
Maximum Thrust Load:	25 lbs
Shaft Run Out:	0.001 inch T.I.R. max
Radial Play:	0.001 inch max w/ 1.0 lb load
End Blove	0.001 inch max w/ 0.0 lb load

End Play:	0.001 mcm max w/ 9.0 ib load
Perpendicularity:	0.003 inches
Concentricity:	0.002 inches

Downloads

Family Datasheet:	StepMotorWiring-6-lead.pdf
Datasheet:	http://s3.amazonaws.com/applied-motion-pdf/4023-998.pdf
2D Drawing:	₫ 4023 998 revD.pdf

Pricing

	4023-998 Part No. w/ Single Shaft
1pc.	\$50.00
25pc.	
50pc.	
100pc.	Request a Quote for 100+ piece pricing.