

M3H & MH Series


8 pin DIP, 3.3 or 5.0 Volt, HCMOS/TTL Clock Oscillator



- 3.3 or 5.0 Volt Versions
- RoHS Compliant Version available
- Low Jitter

Ordering Information		00.0000
	M3H / MH	1 3 F A D -R MHz
Product Series	M3H = 3.3 Volt MH = 5.0 Volt	
Temperature Range	1: 0°C to +70°C 2: -40°C to +85°C 3: -55°C to +105°C 4: -55°C to +125°C 5: -10°C to +85°C 6: -20°C to +70°C 7: 0°C to +85°C	
Stability	1: ±1000 ppm 2: ±500 ppm 3: ±100 ppm 4: ±50 ppm 5: ±35 ppm 6: ±25 ppm 7: +0/-200 ppm * 8: ±20 ppm	
Output Type	F: Fixed T: Tristate	
Symmetry/Logic Compatibility	A: 40/60 HCMOS/TTL B: 45/55 TTL (MH series only) C: 45/55 HCMOS D: 45/55 HCMOS/TTL (MH to 50 MHz only)	
Package/Lead Configurations	D: DIP; Nickel Header G: Gull Wing; Nickel Header	
RoHS Compliance	Blank: non-RoHS compliant part -R: RoHS compliant part	
Frequency (customer specified)		

*Contact factory for availability



Pin Connections

PIN	FUNCTION
1	N/C or Tristate
4	Circuit/Case Ground
5	Output
8	+Vdd

PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
Frequency Range	F	1.5 1.0		100 80	MHz MHz	M3H MH See Note 1
Operating Temperature	Ta	(See Ordering Information)				
Storage Temperature	Ts	-55		+125	°C	
Frequency Stability	ΔF/F	(See Ordering Information)				
Aging						
1st Year			±3		ppm	
Thereafter (per year)			±2		ppm	
Input Voltage	Vdd	3.135 4.5	3.3 5.0	3.465 5.5	V V	M3H MH
Input Current (M3H)	Idd			25 35 55	mA mA mA	1.500 to 50.000 MHz 50.001 to 67.000 MHz 67.001 to 100.000 MHz
Input Current (MH)	Idd			40 60	mA mA	1.000 to 40.000 MHz 40.001 to 80.000 MHz
Output Type						HCMOS/TTL
Load		2 TTL or 15 pF 10 TTL or 50 pF				M3H MH See Note 2
Symmetry (Duty Cycle)		(See Ordering Information)				See Note 3
Logic "1" Level	Voh	90% Vdd Vdd - 0.5			V V	HCMOS Load TTL Load
Logic "0" Level	Vol			10% Vdd 0.5	V V	HCMOS Load TTL Load
Output Current				±4 ±16	mA mA	M3H MH
Rise/Fall Time	Tr/Tf			10	ns	See Note 4
Tristate Function		Input Logic "1" or floating; output active Input Logic "0"; output disables to high-Z				
Start up Time			5		ms	
Random Jitter	Rj		5	12	ps RMS	1-Sigma

1. Contact the factory for availability of higher frequencies.
2. TTL load - See load circuit diagram #1. HCMOS load - See load circuit diagram #2.
3. Symmetry is measured at 1.4 V with TTL load, and at 50% Vdd with HCMOS load.
4. Rise/Fall times are measured between 0.4 V and 2.4 V with TTL load, and between 10% Vdd and 90% Vdd with HCMOS load.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.