



SPECIFICATIONS

1. Rating : DC 30V 1.5A
2. Contact Resistance: $\leq 50m\Omega$
3. Insulation Resistance: $\geq 1000m\Omega$ Min DC250V
4. Operating Temperature Range: $-40^{\circ}C + 85^{\circ}C$

③	Shell	—	1	SPCC			
②	Contact	—	4	BRASS			
①	Housing	—	1	PBT	Blue		
ITEM	PART NAME	TER.NO.	QTY.	MATERIAL	FINISHING	REMARK	
APPROVALS		DATE					
DRAWN	QFENG.XU	2020/7/1					
CHECKED							
TITLE:		USB CONNECTOR					
PART NO.		U-G-09WS-W-1					
UNIT:		mm					
SCALE:		1:1					
DRAWING NO.							



ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
TOLERANCES ARE 30~Ø以上 ±0.30 ANGLE 10~30 ±0.25 5~10 ±0.20 ±2° ~3 ±0.15						
APPROVALS						
CHECKED						
DRAWN						
DATE						
PART NO.		U-G-09WS-W-1				
UNIT:		mm				
SCALE:		1:1				
DRAWING NO.						
PROJ.						
SHEET		1 OF 1				