

GMI6027P-2C 全指向驻积体咪头

详情说明

| No. | Item | Symbol | Unit | Specification | Condition |
|-----|----------------------------|--------|------|-----------------|----------------------------------|
| 1 | Directivity | | | Omnidirectional | |
| 2 | Sensitivity | S | dB | -34~-44±2 | f=1KHz, 1Pa 0dB=1V/Pa |
| 3 | Standard operating voltage | Vs | V | 2.0 | |
| 4 | Output impedance | Zout | KΩ | ≤2.2 | f=1KHz, 1Pa |
| 5 | Frequency | | Hz | 100-10000 | |
| 6 | Max operating voltage | | V | 10 | |
| 7 | Sensitivity reduction | ΔS-Vs | dB | -3 | f=1KHz, 1Pa Vs=1.5VDC to 3VDC |
| 8 | Max. current consumption | IDSS | mA | ≤0.5 | |
| 9 | Signal to noise ration | S/N | dBA | ≥58 | f=1KHz, P _{in} =1Pa |
| 10 | Max. Sound Pressure Level | S.P.L | dB | 110 | |
| 11 | Operation temp. | | ℃ | -20 ~+60 | |
| 12 | Storage temp. | | ℃ | -30 ~+70 | |
| 13 | Dimension | | mm | ∅ 6.0 x 2.7 | See appearance drawing |
| 14 | Terminal | | | Terminal | See appearance drawing |