

**ELFA artikelnr.**

SIDA: 1/10

50-151-10 EMC-list Slot 77-010-02
50-151-28 EMC-list Slot 77-011-02
50-151-69 EMC-list River 97-955-02
50-152-01 EMC-list All 97-500-02
50-152-19 EMC-list All 97-520-02
50-152-27 EMC-list All 97-537-02
50-152-35 EMC-list Large 97-438-02
50-152-43 EMC-list Large 97-440-02
50-152-50 EMC-list Twist 97-550-02
50-152-68 EMC-list Twist 97-556-02
50-152-76 EMC-list Twist 97-558-02
50-152-84 EMC-list Twist 97-559-02
50-152-92 EMC-list ClipOn 97-604-02
50-153-00 EMC-list ClipOn 97-610-02
50-153-18 EMC-list ClipOn 97-620-02

50-153-26 EMC-list ClipOn 97-630-02
50-154-09 EMC-list ClipOn 97-655-02
50-154-17 EMC-list ClipOn 97-656-02
50-154-25 EMC-list ClipOn 97-976-02
50-154-33 EMC-list ClipOn 97-974-02
50-154-41 EMC-list D-sub 9p SS
50-154-58 EMC-list D-sub 15p SS
50-154-66 EMC-list D-sub 25p SS
50-154-74 EMC-list D-sub 37p SS
50-154-82 EMC-list D-sub 50p SS
50-154-90 EMC-list DIN Kont. Large
50-155-08 EMC-list DIN Kont. Mini
50-155-16 EMC-list Contact 97-221
50-155-24 EMC-list Contact 97-390



**Instrument
Specialties**Where Shielding
is a Science.


Slot Mount Series

Slot Mount Series Dimensions

Series	A	B	C	D	E	H	M	Recommended			Approx. Length	# of Fingers
								*N	*O	*P		
77-010	.320 (8.13)	.110 (2.79)	.004 (0.10)	.187 (4.75)	.018 (0.46)	.085 (2.16)	.110 (2.79)	.090 (2.29)	.260 (6.60)	.040 (1.02)	.16 (406)	86
77-011	.600 (15.24)	.220 (5.59)	.005 (0.13)	.282 (7.16)	.032 (0.81)	.140 (3.56)	.180 (4.57)	.090 (2.29)	.520 (13.21)	.070 (1.78)	.16 (406)	57
77-015	.600 (15.24)	.220 (5.59)	.005 (0.13)	.282 (7.16)	.032 (0.81)	.140 (3.56)	.180 (4.57)	.090 (2.29)	.520 (13.21)	.070 (1.78)	.250 (6.35)	1
77-016	.320 (8.13)	.110 (2.79)	.004 (0.10)	.187 (4.75)	.018 (0.46)	.085 (2.16)	.110 (2.79)	.090 (2.29)	.260 (6.60)	.040 (1.02)	.169 (4.29)	1
77-017	.320 (8.13)	.110 (2.79)	.004 (0.10)	.187 (4.75)	.018 (0.46)	.085 (2.16)	.110 (2.79)	.090 (2.29)	.260 (6.60)	.040 (1.02)	.356 (9.04)	2
77-018	.320 (8.13)	.110 (2.79)	.004 (0.10)	.187 (4.75)	.018 (0.46)	.085 (2.16)	.110 (2.79)	.090 (2.29)	.260 (6.60)	.040 (1.02)	.543 (13.79)	3
77-019	.320 (8.13)	.110 (2.79)	.004 (0.10)	.187 (4.75)	.018 (0.46)	.085 (2.16)	.110 (2.79)	.090 (2.29)	.260 (6.60)	.040 (1.02)	.730 (18.54)	4
77-020	.600 (15.24)	.220 (5.59)	.005 (0.13)	.282 (7.16)	.032 (0.81)	.140 (3.56)	.180 (4.57)	.090 (2.29)	.520 (13.21)	.070 (1.78)	.532 (13.51)	2
77-021	.320 (8.13)	.110 (2.79)	.004 (0.10)	.187 (4.75)	.018 (0.46)	.085 (2.16)	.110 (2.79)	.090 (2.29)	.260 (6.60)	.060 (1.52)	.16 (406)	86

*May vary depending upon application.

Top View**Right View**



Symmetrical Slotted Shielding (S³)


S3 Series Sticky Fingers®

Series	A	B Min.	C	D	E	K	L	Approx. Length
97-951	.62 (15.8)	.22 (5.6)	.004 (0.10)	.375 (9.53)	.030 (0.76)	.76 (19.3)	.10 (2.5)	15 (381)
97-954	.45 (11.4)	.14 (3.6)	.003 (0.08)	.250 (6.35)	.022 (0.56)	.51 (13.0)	.070 (1.78)	15 (381)
97-957	.35 (8.9)	.11 (2.8)	.003 (0.08)	.187 (4.75)	.018 (0.46)	.38 (9.6)	.055 (1.40)	15 (381)

S3 Series Rivet Mount


Series	A	B Min.	C	D	E	K	L	Approx. Length	M	N	No. of Rivets
97-952	.62 (15.8)	.22 (5.6)	.004 (0.10)	.375 (9.53)	.030 (0.76)	.76 (19.3)	.10 (2.5)	15 (381)	.56 (14.2)	.94 (23.9)	10
97-955	.45 (11.4)	.14 (3.6)	.003 (0.08)	.250 (6.35)	.022 (0.56)	.51 (13.0)	.070 (1.78)	15 (381)	.63 (16.0)	.88 (22.4)	10
97-958	.35 (8.9)	.11 (2.8)	.003 (0.08)	.187 (4.75)	.018 (0.46)	.38 (9.6)	.07 (1.8)	15 (381)	.66 (16.8)	.84 (21.3)	10


* Two rivet types are available. Consult sales department for further information.



All-Purpose Gaskets

Series	A	B	C	D	E	F	G	H	I Dia.	J	K	L	Approx. Length in. (mm)	Approx. Coil ft. (m)
97-500	.60 (15.2)	.23 (5.8)	.004 (0.10)	.375 (9.53)	.032 (0.81)	.38 (9.7)	.31 (7.9)	.50 (12.7)	.08 (2.0)	.500 (12.70)	.77 (19.6)	.040 (1.02)	24 (610)	25 (7.6)
97-520	.37 (9.4)	.14 (3.6)	.003 (0.08)	.250 (6.35)	.022 (0.56)	.25 (6.4)	.09 (2.3)	.31 (7.9)	.06 (1.5)	.320 (8.13)	.50 (12.7)	.070 (1.78)	16 (406)	25 (7.6)
97-536	.67 (17.0)	.31 (7.9)	.004 (0.10)	.375 (9.53)	.040 (1.02)	.38 (9.7)	.38 (9.7)	.53 (13.5)	.14 (3.6)	—	.94 (23.9)	.140 (3.56)	24 (610)	25 (7.6)
97-537	1.13 (28.7)	.41 (10.4)	.007 (0.18)	.500 (12.70)	.040 (1.02)	.50 (12.7)	.56 (14.2)	.78 (19.8)	.14 (3.6)	.750 (19.05)	1.94 (49.3)	.100 (2.54)	12 (305)	—
97-538	.78 (19.8)	.25 (6.4)	.005 (0.13)	.375 (9.53)	.040 (1.02)	.38 (9.7)	.38 (9.7)	.53 (13.5)	.14 (3.6)	.480 (12.19)	.94 (23.9)	.080 (2.03)	24 (610)	25 (7.6)
97-540	.28 (7.1)	.11 (2.8)	.003 (0.08)	.188 (4.78)	.018 (0.46)	.19 (4.8)	.08 (2.0)	.23 (5.8)	.06 (1.5)	.240 (6.09)	.37 (9.4)	.065 (1.65)	16 (406)	25 (7.6)







Large Enclosure Series


Large Enclosure Series

Series	A Ref.	B Min.	C	D	E	F	G	H Dia.	I	L	Approx. Length ft. (m)
97-438	1.09 (27,7)	.25 (6,4)	.005 (0,13)	.375 (9,53)	.040 (1,02)	.16 (4,1)	.38 (9,7)	.14 (3,6)	1.27 (32,3)	.08 (2,0)	25 (7,6)
97-440	1.63 (41,4)	.41 (10,4)	.007 (0,18)	.500 (12,7)	.040 (1,02)	.19 (4,8)	.50 (12,7)	.14 (3,6)	1.90 (48,3)	.10 (2,5)	25 (7,6)




Twist Series


Series	A	B	C	Pitch D	Slot E	H	Approx. Length in. (mm)	Approx. Coil ft. (m)	Gasket
97-550	.23 (5,8)	.03 (0,8)	.003 (0,08)	.095 (2,41)	.015 (0,38)	.14 (3,6)	24 (610)	25 (7,6)	NO
97-551	.16 (4,1)	.03 (0,8)	.003 (0,08)	.095 (2,41)	.015 (0,38)	.08 (2,0)	24 (610)	—	NO
97-555	.34 (8,6)	.07 (1,8)	.003 (0,08)	.165 (4,19)	.015 (0,38)	.18 (4,6)	24 (610)	25 (7,6)	NO
97-556	.34 (8,6)	.07 (1,8)	.003 (0,08)	.165 (4,19)	.015 (0,38)	.18 (4,6)	24 (610)	25 (7,6)	YES
97-558	.20 (5,1)	.07 (1,8)	.003 (0,08)	.165 (4,19)	.015 (0,38)	.11 (2,8)	24 (610)	—	NO
97-559	.30 (7,6)	.07 (1,8)	.003 (0,08)	.165 (4,19)	.015 (0,38)	.18 (4,6)	24 (610)	25 (7,6)	NO
97-560	.50 (12,7)	.07 (1,8)	.003 (0,08)	.165 (4,19)	.015 (0,38)	.19 (4,8)	24 (610)	25 (7,6)	NO
97-561	.50 (12,7)	.07 (1,8)	.003 (0,08)	.165 (4,19)	.015 (0,38)	.19 (4,8)	24 (610)	25 (7,6)	YES



97-551/558



Clip-On Gaskets




Clip-On Series 97/603/604/605/606/607



Clip-On Series


Lance Dimensions																						
Series	A	B	C	D	E	F	G	H	Approx. Length	No Lance		Square Lance	Grip-lite "T" Lance		Snap-lite "D" Lance	Lance Locations Dimensions			Lance to Lance Dims.		Body Style	
										NL	SQ		GT	ST		I	J	K	Slot	Sol.		
97-603	38 (9.7)	20 (5.1)	10 (2.5)	33 (8.4)	.005 (0.13)	.250 (6.35)	.040 (1.02)	.060 (1.52)	16 (406)						X X		.250 (6.35)	.099 (2.53)	.500 (12.70)	X X		
97-604	33 (8.4)	28 (6.7)	.07 (1.8)	38 (9.7)	.005 (0.13)	.250 (6.35)	.040 (1.02)	.100 (2.54)	16 (406)					X X			.230 (5.80)	.204 (5.18)	.500 (12.70)	X X		
97-605	38 (9.7)	20 (5.1)	.07 (1.8)	38 (9.7)	.005 (0.13)	.250 (6.35)	.040 (1.02)	.060 (1.52)	16 (406)					X X			.230 (5.80)	.204 (5.18)	.500 (12.70)	X X		
97-606	38 (9.7)	20 (5.1)	.07 (1.8)	38 (9.7)	.005 (0.13)	.250 (6.35)	.040 (1.02)	.060 (1.52)	16 (406)					X X			.250 (6.35)	.161 (4.08)	.500 (12.70)	X X		
97-607	33 (8.4)	28 (6.7)	.07 (1.8)	38 (9.7)	.005 (0.13)	.250 (6.35)	.040 (1.02)	.100 (2.54)	16 (406)					X X			.250 (6.35)	.161 (4.08)	.500 (12.70)	X X		
97-610	30 (7.6)	10 (2.5)	.07 (1.8)	19 (4.8)	.005 (0.13)	.187 (4.75)	.047 (1.19)	.065 (1.65)	16 (406)		X X			† †							X X	
97-611	30 (7.6)	10 (2.5)	.07 (1.8)	19 (4.8)	.005 (0.13)	.182 (4.62)	.047 (1.19)	.060 (1.52)	16 (406)					X X			.364 (9.25)	.062 (1.57)	.728 (18.49)	X X		
97-612	44 (11.2)	10 (2.5)	.07 (1.8)	19 (4.8)	.003 (0.08)	.187 (4.75)	.047 (1.19)	.045 (1.14)	16 (406)		† †	X X					.093 (2.37)	.050 (1.26)	.750 (19.05)	X X		
97-613	30 (7.6)	10 (2.5)	.07 (1.8)	19 (4.8)	.005 (0.13)	.182 (4.62)	.047 (1.19)	.060 (1.52)	16 (406)					X X			.364 (9.25)	.054 (1.37)	.728 (18.49)	X X		
97-614	30 (7.6)	10 (2.5)	.05 (1.3)	19 (4.8)	.005 (0.13)	.187 (4.75)	.047 (1.19)	.065 (1.65)	16 (406)		X X			† †							X X	
97-619	44 (11.2)	08 (2.0)	.05 (1.3)	19 (4.8)	.005 (0.13)	.187 (4.75)	.047 (1.19)	.045 (1.14)	16 (406)		X X			† †							X X	
97-620	44 (11.2)	08 (2.0)	.07 (1.8)	19 (4.8)	.005 (0.13)	.187 (4.75)	.047 (1.19)	.045 (1.14)	16 (406)		X X			† †							X X	
97-621	44 (11.2)	12 (3.0)	.07 (1.8)	19 (4.8)	.005 (0.13)	.193 (4.90)	.046 (1.17)	.070 (1.78)	16 (406)					X X			.652 (16.56)	.084 (2.13)	1.351 (34.32)	X X		
97-622	44 (11.2)	12 (3.0)	.07 (1.8)	19 (4.8)	.005 (0.13)	.193 (4.90)	.046 (1.17)	.075 (1.91)	16 (406)					X X			.290 (7.37)	.060 (1.52)	.725 (18.42)	X X		
97-628	60 (15.2)	21 (5.3)	.10 (2.5)	19 (4.8)	.005 (0.13)	.187 (4.75)	.047 (1.19)	.070 (1.78)	16 (406)		X X			† †							X X	
97-629	60 (15.2)	21 (5.3)	.05 (1.3)	19 (4.8)	.005 (0.13)	.187 (4.75)	.047 (1.19)	.070 (1.78)	16 (406)		X X			† †							X X	
97-630	60 (15.2)	21 (5.3)	.07 (1.8)	19 (4.8)	.005 (0.13)	.187 (4.75)	.047 (1.19)	.070 (1.78)	16 (406)		X X			† †							X X	
97-631	60 (15.2)	21 (5.3)	.07 (1.8)	19 (4.8)	.005 (0.13)	.182 (4.62)	.047 (1.19)	.080 (2.03)	16 (406)					X X			.364 (9.25)	.058 (1.46)	.728 (18.49)	X X		
97-632	60 (15.2)	21 (5.3)	.07 (1.8)	19 (4.8)	.005 (0.13)	.182 (4.62)	.047 (1.19)	.080 (2.03)	16 (406)					X X			.364 (9.25)	.058 (1.46)	.728 (18.49)	X X		
97-633	60 (15.2)	21 (5.3)	.05 (1.3)	19 (4.8)	.005 (0.13)	.182 (4.62)	.047 (1.19)	.080 (2.03)	16 (406)					X X			.364 (9.25)	.058 (1.46)	.728 (18.49)	X X		
97-634	60 (15.2)	21 (5.3)	.05 (1.3)	19 (4.8)	.005 (0.13)	.182 (4.62)	.047 (1.19)	.080 (2.03)	16 (406)					X X			.364 (9.25)	.058 (1.46)	.728 (18.49)	X X		
97-640	109 (27.7)	26 (6.6)	.07 (1.8)	28 (7.1)	.005 (0.13)	.375 (9.53)	.040 (1.02)	.060 (1.50)	16 (406)		X X			† †							X X	
97-645	21 (5.4)	.07 (1.8)	.045 (1.14)	25 (6.4)	.003 (0.07)	.200 (5.1)	.030 (0.76)	.010 (0.25)	24 (610)					X X			.485 (12.3)	.133 (3.37)	1.000 (25.4)	X X		
97-650	98 (24.9)	40 (10.2)	.20 (5.1)	30 (7.6)	.004 (0.10)	1.00 (25.4)	.030 (0.76)	.20 (5.1)	16 (406)		† †	X X					.192 (4.88)	.120 (3.05)	.486 (12.34)	X X		

† Optional




Clip-On Perpendicular Grounds

97-655






Impedance vs. Frequency



Clip-On Perpendicular Shielding



97-656








Longitudinal Shielding

Clip-On Longitudinal Grounding Strip





Mini-Longitudinal Grounding Gasket



“D” Connector Shields

"D" Connector Series Dimensions


SS	BeCu	# PINS	A	B	C	D	E	F	G
97-768	97-778	9	1.41 (35.8)	.98 (24.9)	.78 (19.8)	.22 (5.6)	.44 (11.2)	.69 (17.5)	.13 (3.2)
97-769	97-779	15	1.74 (44.2)	1.31 (33.3)	1.11 (28.2)	.22 (5.6)	.44 (11.2)	.69 (17.5)	.13 (3.2)
97-770	97-780	25	2.28 (57.9)	1.85 (47.0)	1.65 (41.9)	.22 (5.6)	.44 (11.2)	.69 (17.5)	.13 (3.2)
97-771	97-781	37	2.93 (74.4)	2.50 (63.5)	2.29 (58.2)	.22 (5.6)	.44 (11.2)	.69 (17.5)	.13 (3.2)
97-772	97-782	50	2.84 (72.1)	2.41 (61.2)	2.11 (53.6)	.28 (7.1)	.55 (13.9)	.80 (20.3)	.24 (6.1)






DIN Connector Series


97-725





97-723



*97-725 is available without the formed bends or with bends of varying sizes to accommodate your requirements for a variety of connector sizes.





Contact Strips




97-221

Flat Strip

Series	Fig.	Pitch	Slot	B	Approx. Length (L)	Approx. # of Fingers
97-117	A	.187 (4,75)	.047 (1,19)	.63 (16,0)	16 (406)	86
97-135	E	.135 (3,43)	.040 (1,02)	.23 (5,8)	16 (406)	119
97-221	D	.060 (1,52)	.020 (0,51)	.09 (2,3)	12 (305)	200
97-251	D	.127 (3,23)	.050 (1,27)	.09 (2,3)	12 (305)	95
97-300	A	.165 (4,19)	.040 (1,02)	.19 (4,8)	16 (406)	97
97-310	D	.187 (4,75)	.062 (1,57)	.38 (9,6)	16 (406)	86
97-340	E	.163 (4,14)	.020 (0,51)	.25 (6,4)	16 (406)	98
97-390	E	.134 (3,40)	.040 (1,02)	.23 (5,8)	16 (406)	119



97-390



Load / Deflection Data

Load Charts for EMI Gaskets


Part No.	LARGEST OPENING				DESIGN HEIGHT				SMALLEST OPENING	
	Height	Load	Height	Load	Height	Load	Height	Load	Height	Load
	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)
77-010	0,055 (1,40)	10 (15)	0,045 (1,14)	21 (31)	0,035 (0,89)	34 (51)	0,025 (0,64)	47 (70)	0,015 (0,38)	62 (92)
77-011	0,120 (3,05)	12 (18)	0,095 (2,41)	29 (43)	0,070 (1,78)	48 (71)	0,045 (1,14)	74 (110)	0,020 (0,51)	121 (180)

Load Charts for Grounding Strips

Part No.	SMALLEST DEFLECTION								LARGEST DEFLECTION	
	Deflection	Load	Deflection	Load	Deflection	Load	Deflection	Load	Deflection	Load
	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)
97-221	0,067 (1,70)	18 (27)	0,064 (1,63)	31 (46)	0,061 (1,55)	51 (76)	0,058 (1,47)	66 (98)	0,055 (1,40)	85 (126)
97-390	0,193 (4,90)	23 (34)	0,186 (4,72)	55 (82)	0,179 (4,55)	90 (134)	0,172 (4,37)	138 (205)	0,165 (4,19)	183 (272)

Load Charts for EMI Gaskets

Part No.	LARGEST OPENING				DESIGN HEIGHT				SMALLEST OPENING	
	Height	Load	Height	Load	Height	Load	Height	Load	Height	Load
	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)
97-438	0,215 (5,46)	10 (15)	0,180 (4,57)	22 (33)	0,145 (3,68)	32 (48)	0,110 (2,79)	42 (62)	0,075 (1,91)	60 (89)
97-440	0,35 (8,9)	17 (25)	0,29 (7,2)	31 (46)	0,23 (5,7)	41 (61)	0,16 (4,1)	51 (75)	0,10 (2,5)	64 (95)
97-500	0,190 (4,83)	16 (24)	0,155 (3,94)	26 (39)	0,115 (2,92)	35 (52)	0,080 (2,03)	44 (65)	0,040 (1,02)	53 (78)
97-520	0,125 (3,18)	18 (27)	0,110 (2,79)	32 (48)	0,100 (2,54)	39 (58)	0,085 (2,16)	49 (73)	0,070 (1,78)	59 (88)
97-537	0,35 (8,9)	27 (40)	0,29 (7,2)	47 (69)	0,23 (5,7)	62 (92)	0,16 (4,1)	72 (107)	0,10 (2,5)	87 (129)
97-550	0,026 (0,66)	8 (12)	0,022 (0,56)	14 (21)	0,018 (0,46)	25 (37)	0,014 (0,36)	33 (49)	0,010 (0,25)	48 (71)
97-556	0,063 (1,60)	29 (42)	0,056 (1,42)	46 (68)	0,049 (1,24)	64 (94)	0,042 (1,07)	82 (122)	0,035 (0,89)	123 (183)
97-558	0,063 (1,60)	10 (15)	0,056 (1,42)	21 (31)	0,049 (1,24)	37 (55)	0,042 (1,07)	46 (68)	0,035 (0,89)	52 (77)
97-559	0,064 (1,63)	11 (17)	0,058 (1,47)	21 (32)	0,052 (1,32)	32 (47)	0,046 (1,17)	39 (58)	0,040 (1,02)	45 (66)



Load / Deflection Data

Load Charts for EMI Gaskets

Part No.	LARGEST OPENING				DESIGN HEIGHT				SMALLEST OPENING	
	Height	Load	Height	Load	Height	Load	Height	Load	Height	Load
	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)	Inches (mm)	Lb/Ft (Kg/m)
97-604	0.245 (6,22)	6 (9)	0.210 (5,33)	13 (19)	0.170 (4,32)	22 (33)	0.135 (3,43)	30 (45)	0.100 (2,54)	40 (60)
97-610	0.093 (2,36)	3 (4)	0.086 (2,18)	11 (16)	0.079 (2,01)	23 (34)	0.072 (1,83)	37 (55)	0.065 (1,65)	69 (103)
97-620	0.073 (1,85)	32 (48)	0.066 (1,68)	75 (112)	0.059 (1,50)	118 (176)	0.052 (1,32)	170 (253)	0.045 (1,14)	205 (305)
97-630	0.180 (4,57)	3 (4)	0.155 (3,94)	6 (9)	0.125 (3,18)	11 (16)	0,100 (2,54)	16 (24)	0,070 (1,78)	25 (37)
97-655	0.080 (2,03)	37 (55)	0.070 (1,78)	27 (40)	0.060 (1,52)	17 (25)	0.050 (1,27)	8 (12)	0.040 (1,02)	4 (6)
97-955	0.126 (3,20)	11 (16)	0.112 (2,84)	21 (31)	0.098 (2,49)	28 (42)	0.084 (2,13)	37 (55)	0.070 (1,78)	62 (92)
97-974	0.130 (3,30)	0.8 (1,2)	0.110 (2,79)	1.5 (2,2)	0.090 (2,29)	2.5 (3,7)	0.070 (1,78)	3.6 (5,4)	0.050 (1,27)	5.1 (7,6)
97-976	0.145 (3,68)	1.4 (2,1)	0.115 (2,92)	3.1 (4,6)	0.080 (2,03)	5.0 (7,4)	0.050 (1,27)	6.6 (9,8)	0.020 (0,51)	8.9 (13,2)