




GPDR3520

RECTIFIER DIODE



VOLTAGE UP TO **2400 V**
 AVERAGE CURRENT **5200 A**
 SURGE CURRENT **70 kA**

BLOCKING CHARACTERISTICS

Characteristic	Conditions	Value
V _{RRM}	Repetitive peak reverse voltage	2400 V
V _{RSM}	Non-repetitive peak reverse voltage	2500 V
I _{RRM}	Repetitive peak reverse current, max.	V _{RRM} , single phase, half wave, T _j = T _{jmax} 150 mA

FORWARD CHARACTERISTICS

I _{F(AV)}	Average forward current	Sine wave, 180° conduction, T _h = 55°C	5200 A
I _{F(RMS)}	R.M.S. forward current	Sine wave, 180° conduction, T _h = 55°C	8168 A
I _{FSM}	Surge forward current	Non rep. half sine wave, 50 Hz, V _R = 0 V, T _j = T _{jmax}	70 kA
I ² t	I ² t for fusing coordination		24500 kA ² s
V _{F(TO)}	Threshold voltage	T _j = T _{jmax}	0.64 V
r _F	Forward slope resistance	T _j = T _{jmax}	0.14 mΩ
V _{FM}	Peak forward voltage, max	Forward current I _F = 4000 A, T _j = T _{jmax}	1.20 V


SWITCHING CHARACTERISTICS

Q _{rr}	Rverse recovery charge, typ	T _j = T _{jmax} , I _F = 2000 A, di/dt = -5 A/μs	250 μC
I _{rr}	Reverse recovery current	V _R = 100 V	A
t _{rr}	Reverse recovery time		μs
V _{FP}	Forward recovery voltage	T _j = T _{jmax} , di/dt = A/μs	V


THERMAL AND MECHANICAL CHARACTERISTICS

R _{th(j-c)}	Thermal resistance (junction to case)	Double side cooled	0.008 °C/W
R _{th(c-h)}	Thermal resistance (case to heatsink)	Double side cooled	0.002 °C/W
T _{jmax}	Max operating junction temperature		175 °C
T _{stg}	Storage temperature		-40 / 175 °C
F	Clamping force ± 10%		50 kN
	Mass		1200 g


Current rating - sine wave




Power loss - sine wave





Maximum surge current
d.s. cooled



Forward voltage drop



Thermal Impedance (j-c)



Ordering information GPDR3520-VV

VV: blocking voltage / 100 (e.g. 24 for 2400V)

In the interest of product improvement Green Power Solutions reserves the right to change any specification given in this data sheet without notice.