Document Title

512Kx36 & 1Mx18-Bit Synchronous Pipelined Burst SRAM

Revision History

Rev. No.	History	Draft Date	Remark
0.0	Initial draft	Dec. 29. 1998	Preliminary
0.1	1. Update ICC & ISB values.	May. 27. 1999	Preliminary
0.2	1. Change I_{SB} value from 150mA to 110mA at -67. 2. Change I_{SB} value from 130mA to 90mA at -72 . 3. Change I_{SB} value from 120mA to 80mA at -10 .	Sep. 04. 1999	Preliminary
0.3	1. Add tCYC 167MHz and 183MHz. 2. Changed DC condition at Icc and parameters Icc ; from 420mA to 400mA at -67, from 400mA to 380mA at -72, from 350mA to 320mA at -10,	Nov. 19. 1999	Preliminary
1.0	1. Final Spec Release.	Dec. 08. 1999	Final

The attached data sheets are prepared and approved by SAMSUNG Electronics. SAMSUNG Electronics CO., LTD. reserve the right to change the specifications. SAMSUNG Electronics will evaluate and reply to your requests and questions on the parameters of this device. If you have any questions, please contact the SAMSUNG branch office near your office, call or contact Headquarters.

512Kx36 & 1Mx18-Bit Synchronous Pipelined Burst SRAM

FEATURES

- Synchronous Operation.
- 2 Stage Pipelined operation with 4 Burst.
- On-Chip Address Counter.
- Self-Timed Write Cycle.
- On-Chip Address and Control Registers.
- V_{DD}= 3.3V +0.165V/-0.165V Power Supply.
- I/O Supply Voltage 3.3V +0.165V/-0.165V for 3.3V I/O or 2.5V+0.4V/-0.125V for 2.5V I/O.
- 5V Tolerant Inputs Except I/O Pins.
- Byte Writable Function.
- Global Write Enable Controls a full bus-width write.
- Power Down State via ZZ Signal.
- $\overline{LBO}$ Pin allows a choice of either a interleaved burst or a linear burst.
- Three Chip Enables for simple depth expansion with No Data Contention only for TQFP ; 2cycle Enable, 1cycle Disable.
- Asynchronous Output Enable Control.
- $\overline{ADSP}$, $\overline{ADSC}$, $\overline{ADV}$ Burst Control Pins.
- TTL-Level Three-State Output.
- 100-TQFP-1420A / 119BGA(7x17 Ball Grid Array Package)

FAST ACCESS TIMES

PARAMETER	Symbol	-54	-60	-67	-72	-10	Unit
Cycle Time	t_{CYC}	5.4	6.0	6.7	7.2	10	ns
Clock Access Time	t_{CD}	3.3	3.5	3.8	4.0	4.5	ns
Output Enable Access Time	t_{OE}	3.3	3.5	3.8	4.0	4.5	ns

GENERAL DESCRIPTION

The KM736V989 and KM718V089 are 18,874,368-bit Synchronous Static Random Access Memory designed for high performance second level cache of Pentium and Power PC based System.

It is organized as 512K(1M) words of 36(18) bits and integrates address and control registers, a 2-bit burst address counter and added some new functions for high performance cache RAM applications; $\overline{GW}$, $\overline{BW}$, $\overline{LBO}$, ZZ. Write cycles are internally self-timed and synchronous.

Full bus-width write is done by $\overline{GW}$, and each byte write is performed by the combination of $\overline{WE}$x and $\overline{BW}$ when $\overline{GW}$ is high. And with $\overline{CS_1}$ high, $\overline{ADSP}$ is blocked to control signals.


Burst cycle can be initiated with either the address status processor($\overline{ADSP}$) or address status cache controller($\overline{ADSC}$) inputs. Subsequent burst addresses are generated internally in the system′s burst sequence and are controlled by the burst address advance($\overline{ADV}$) input.

$\overline{LBO}$ pin is DC operated and determines burst sequence(linear or interleaved).


ZZ pin controls Power Down State and reduces Stand-by current regardless of CLK.

The KM736V989 and KM718V089 are fabricated using SAMSUNG′s high performance CMOS technology and is available in a 100pin TQFP and 119BGA package. Multiple power and ground pins are utilized to minimize ground bounce.

LOGIC BLOCK DIAGRAM



PIN CONFIGURATION(TOP VIEW)




PIN NAME

SYMBOL	PIN NAME	TQFP PIN NO.	SYMBOL	PIN NAME	TQFP PIN NO.
A_0 - A_{18}	Address Inputs	32,33,34,35,36,37,42 43,44,45,46,47,48,49 50,81,82,99,100	V_{DD}	Power Supply(+3.3V)	15,41,65,91
			V_{SS}	Ground	17,40,67,90
$\overline{ADV}$	Burst Address Advance	83	N.C.	No Connect	14,16,38,39,66
$\overline{ADSP}$	Address Status Processor	84			
$\overline{ADSC}$	Address Status Controller	85	$DQa_{0\sim a7}$	Data Inputs/Outputs	52,53,56,57,58,59,62,63
$\overline{CLK}$	Clock	89	$DQb_{0\sim b7}$		68,69,72,73,74,75,78,79
$\overline{CS_1}$	Chip Select	98	$DQc_{0\sim c7}$		2,3,6,7,8,9,12,13
$\overline{CS_2}$	Chip Select	97	$DQd_{0\sim d7}$		18,19,22,23,24,25,28,29
$\overline{CS_2}$	Chip Select	92	$DQPa\sim P_d$		51,80,1,30
$\overline{WE}$x(x=a,b,c,d)	Byte Write Inputs	93,94,95,96			
$\overline{OE}$	Output Enable	86	V_{DDQ}	Output Power Supply (3.3V or 2.5V)	4,11,20,27,54,61,70,77
$\overline{GW}$	Global Write Enable	88			
$\overline{BW}$	Byte Write Enable	87	V_{SSQ}	Output Ground	5,10,21,26,55,60,71,76
$\overline{ZZ}$	Power Down Input	64			
LBO	Burst Mode Control	31			

Note : 1. A0 and A1 are the two least significant bits(LSB) of the address field and set the internal burst counter if burst is desired.

SAMSUNG ELECTRONICS

PIN CONFIGURATION(TOP VIEW)



PIN NAME

SYMBOL	PIN NAME	TQFP PIN NO.	SYMBOL	PIN NAME	TQFP PIN NO.
A_0 - A_{19}	Address Inputs	32,33,34,35,36,37,42 43,44,45,46,47,48,49 50 80,81,82,99,100	V_{DD}	Power Supply(+3.3V)	15,41,65,91
			V_{SS}	Ground	17,40,67,90
$\overline{ADV}$	Burst Address Advance	83	N.C.	No Connect	1,2,3,6,7,14,16,25,28,29 30,38,39,51,52,53,56,57 66,75,78,79,95,96
$\overline{ADSP}$	Address Status Processor	84			
$\overline{ADSC}$	Address Status Controller	85			
$\overline{CLK}$	Clock	89			
$\overline{CS_1}$	Chip Select	98	DQa_0 ~ a_7	Data Inputs/Outputs	58,59,62,63,68,69,72,73
$\overline{CS_2}$	Chip Select	97	DQb_0 ~ b_7		8,9,12,13,18,19,22,23
$\overline{CS_2}$	Chip Select	92	DQPa, Pb		74,24
$\overline{WE}$x(x=a,b)	Byte Write Inputs	93,94			
$\overline{OE}$	Output Enable	86	V_{DDQ}	Output Power Supply (3.3V or 2.5V)	4,11,20,27,54,61,70,77
$\overline{GW}$	Global Write Enable	88			
$\overline{BW}$	Byte Write Enable	87	V_{SSQ}	Output Ground	5,10,21,26,55,60,71,76
$\overline{ZZ}$	Power Down Input	64			
$\overline{LBO}$	Burst Mode Control	31			

Note : 1. A_0 and A_1 are the two least significant bits(LSB) of the address field and set the internal burst counter if burst is desired.

SAMSUNG ELECTRONICS

119BGA PACKAGE PIN CONFIGURATIONS(TOP VIEW)

KM736V989(512Kx36)

	1	2	3	4	5	6	7
A	V_{DDQ}	A	A	$\overline{ADSP}$	A	A	V_{DDQ}
B	NC	A	A	$\overline{ADSC}$	A	A	NC
C	NC	A	A	V_{DD}	A	A	NC
D	DQc	DQPc	V_{SS}	NC	V_{SS}	DQPb	DQb
E	DQc	DQc	V_{SS}	$\overline{CS_1}$	V_{SS}	DQb	DQb
F	V_{DDQ}	DQc	V_{SS}	$\overline{OE}$	V_{SS}	DQb	V_{DDQ}
G	DQc	DQc	$\overline{WE}$c	$\overline{ADV}$	$\overline{WE}$b	DQb	DQb
H	DQc	DQc	V_{SS}	$\overline{GW}$	V_{SS}	DQb	DQb
J	V_{DDQ}	V_{DD}	NC	V_{DD}	NC	V_{DD}	V_{DDQ}
K	DQd	DQd	V_{SS}	CLK	V_{SS}	DQa	DQa
L	DQd	DQd	$\overline{WE}$d	NC	$\overline{WE}$a	DQa	DQa
M	V_{DDQ}	DQd	V_{SS}	$\overline{BW}$	V_{SS}	DQa	V_{DDQ}
N	DQd	DQd	V_{SS}	A_1*	V_{SS}	DQa	DQa
P	DQd	DQPd	V_{SS}	A_0*	V_{SS}	DQPa	DQa
R	NC	A	$\overline{LBO}$	V_{DD}	NC	A	NC
T	NC	NC	A	A	A	NC	ZZ
U	V_{DDQ}	NC	NC	NC	NC	NC	V_{DDQ}

Note : * A_0 and A_1 are the two least significant bits(LSB) of the address field and set the internal burst counter if burst is desired.

PIN NAME

SYMBOL	PIN NAME	SYMBOL	PIN NAME
A	Address Inputs	V_{DD}	Power Supply(+3.3V)
A_0, A_1	Burst Count Address	V_{SS}	Ground
$\overline{ADV}$	Burst Address Advance	N.C.	No Connect
$\overline{ADSP}$	Address Status Processor		
$\overline{ADSC}$	Address Status Controller	DQa	Data Inputs/Outputs
CLK	Clock	DQb	Data Inputs/Outputs
$\overline{CS_1}$	Chip Select	DQc	Data Inputs/Outputs
$\overline{WE}$x	Byte Write Inputs	DQd	Data Inputs/Outputs
(x=a,b,c,d)		DQPa~Pd	Data Inputs/Outpus
$\overline{OE}$	Output Enable	V_{DDQ}	Output Power Supply
$\overline{GW}$	Global Write Enable		(2.5V or 3.3V)
$\overline{BW}$	Byte Write Enable		
$\overline{ZZ}$	Power Down Input		
$\overline{LBO}$	Burst Mode Control		

119BGA PACKAGE PIN CONFIGURATIONS(TOP VIEW)

KM718V089(1Mx18)

	1	2	3	4	5	6	7
A	V_{DDQ}	A	A	$\overline{ADSP}$	A	A	V_{DDQ}
B	NC	A	A	$\overline{ADSC}$	A	A	NC
C	NC	A	A	V_{DD}	A	A	NC
D	DQb	NC	V_{SS}	NC	V_{SS}	DQPa	NC
E	NC	DQb	V_{SS}	$\overline{CS_1}$	V_{SS}	NC	DQa
F	V_{DDQ}	NC	V_{SS}	$\overline{OE}$	V_{SS}	DQa	V_{DDQ}
G	NC	DQb	$\overline{WEb}$	$\overline{ADV}$	V_{SS}	NC	DQa
H	DQb	NC	V_{SS}	$\overline{GW}$	V_{SS}	DQa	NC
J	V_{DDQ}	V_{DD}	NC	V_{DD}	NC	V_{DD}	V_{DDQ}
K	NC	DQb	V_{SS}	CLK	V_{SS}	NC	DQa
L	DQb	NC	V_{SS}	NC	$\overline{WEa}$	DQa	NC
M	V_{DDQ}	DQb	V_{SS}	$\overline{BW}$	V_{SS}	NC	V_{DDQ}
N	DQb	NC	V_{SS}	A_1*	V_{SS}	DQa	NC
P	NC	DQPb	V_{SS}	A_0*	V_{SS}	NC	DQa
R	NC	A	$\overline{LBO}$	V_{DD}	NC	A	NC
T	NC	A	A	NC	A	A	ZZ
U	V_{DDQ}	NC	NC	NC	NC	NC	V_{DDQ}

Note : * A_0 and A_1 are the two least significant bits(LSB) of the address field and set the internal burst counter if burst is desired.

PIN NAME

SYMBOL	PIN NAME	SYMBOL	PIN NAME
A	Address Inputs	V_{DD}	Power Supply(+3.3V)
A_0,A_1	Burst Count Address	V_{SS}	Ground
$\overline{ADV}$	Burst Address Advance	N.C.	No Connect
$\overline{ADSP}$	Address Status Processor		
$\overline{ADSC}$	Address Status Controller	DQa	Data Inputs/Outputs
CLK	Clock	DQb	Data Inputs/Outputs
$\overline{CS_1}$	Chip Select	DQPa~Pb	Data Inputs/Outpus
$\overline{WEx}$ (x=a,b)	Byte Write Inputs	V_{DDQ}	Output Power Supply (2.5V or 3.3V)
$\overline{OE}$	Output Enable		
$\overline{GW}$	Global Write Enable		
$\overline{BW}$	Byte Write Enable		
$\overline{ZZ}$	Power Down Input		
$\overline{LBO}$	Burst Mode Control		

FUNCTION DESCRIPTION

The KM736V989 and KM718V089 are synchronous SRAM designed to support the burst address accessing sequence of the Power PC based microprocessor. All inputs (with the exception of $\overline{OE}$, $\overline{LBO}$ and ZZ) are sampled on rising clock edges. The start and duration of the burst access is controlled by $\overline{ADSC}$, $\overline{ADSP}$ and $\overline{ADV}$ and chip select pins.

The accesses are enabled with the chip select signals and output enabled signals. Wait states are inserted into the access with $\overline{ADV}$.

When ZZ is pulled high, the SRAM will enter a Power Down State. At this time, internal state of the SRAM is preserved. When ZZ returns to low, the SRAM normally operates after 2cycles of wake up time. ZZ pin is pulled down internally.

Read cycles are initiated with $\overline{ADSP}$(regardless of $\overline{WE}$x and $\overline{ADSC}$)using the new external address clocked into the on-chip address register whenever $\overline{ADSP}$ is sampled low, the chip selects are sampled active, and the output buffer is enabled with $\overline{OE}$. In read operation the data of cell array accessed by the current address, registered in the Data-out registers by the positive edge of CLK, are carried to the Data-out buffer by the next positive edge of CLK. The data, registered in the Data-out buffer, are projected to the output pins. $\overline{ADV}$ is ignored on the clock edge that samples $\overline{ADSP}$ asserted, but is sampled on the subsequent clock edges. The address increases internally for the next access of the burst when $\overline{WE}$x are sampled High and $\overline{ADV}$ is sampled low. And $\overline{ADSP}$ is blocked to control signals by disabling $\overline{CS}_1$.

All byte write is done by $\overline{GW}$(regaedless of $\overline{BW}$ and $\overline{WE}$x.), and each byte write is performed by the combination of $\overline{BW}$ and $\overline{WE}$x when $\overline{GW}$ is high.

Write cycles are performed by disabling the output buffers with $\overline{OE}$ and asserting $\overline{WE}$x. $\overline{WE}$x are ignored on the clock edge that samples $\overline{ADSP}$ low, but are sampled on the subsequent clock edges. The output buffers are disabled when $\overline{WE}$x are sampled Low(regaedless of $\overline{OE}$). Data is clocked into the data input register when $\overline{WE}$x sampled Low. The address increases internally to the next address of burst, if both $\overline{WE}$x and $\overline{ADV}$ are sampled Low. Individual byte write cycles are performed by any one or more byte write enable signals($\overline{WE}$a, $\overline{WE}$b, $\overline{WE}$c or $\overline{WE}$d) sampled low. The $\overline{WE}$a control DQa_0 ~ DQa_7 and DQPa, $\overline{WE}$b controls DQb_0 ~ DQb_7 and DQPb, $\overline{WE}$c controls DQc_0 ~ DQc_7 and DQPc, and $\overline{WE}$d control DQd_0 ~ DQd_7 and DQPd. Read or write cycle may also be initiated with $\overline{ADSC}$, instead of $\overline{ADSP}$. The differences between cycles initiated with $\overline{ADSC}$ and $\overline{ADSP}$ as are follows;

- $\overline{ADSP}$ must be sampled high when $\overline{ADSC}$ is sampled low to initiate a cycle with $\overline{ADSC}$.
- $\overline{WE}$x are sampled on the same clock edge that sampled $\overline{ADSC}$ low(and $\overline{ADSP}$ high).

Addresses are generated for the burst access as shown below, The starting point of the burst sequence is provided by the external address. The burst address counter wraps around to its initial state upon completion. The burst sequence is determined by the state of the $\overline{LBO}$ pin. When this pin is Low, linear burst sequence is selected. When this pin is High, Interleaved burst sequence is selected.

BURST SEQUENCE TABLE

(Interleaved Burst)

$\overline{LBO}$ PIN	HIGH	Case 1		Case 2		Case 3		Case 4	
		A_1	A_0	A_1	A_0	A_1	A_0	A_1	A_0
First Address		0	0	0	1	1	0	1	1
↓		0	1	0	0	1	1	1	0
		1	0	1	1	0	0	0	1
Fourth Address		1	1	1	0	0	1	0	0

(Linear Burst)

$\overline{LBO}$ PIN	LOW	Case 1		Case 2		Case 3		Case 4	
		A_1	A_0	A_1	A_0	A_1	A_0	A_1	A_0
First Address		0	0	0	1	1	0	1	1
↓		0	1	1	0	1	1	0	0
		1	0	1	1	0	0	0	1
Fourth Address		1	1	0	0	0	1	1	0

Note : 1. $\overline{LBO}$ pin must be tied to High or Low, and Floating State must not be allowed.

ASYNCHRONOUS TRUTH TABLE

Operation	ZZ	$\overline{OE}$	I/O STATUS
Sleep Mode	H	X	High-Z
Read	L	L	DQ
	L	H	High-Z
Write	L	X	Din, High-Z
Deselected	L	X	High-Z

Notes

1. X means "Don't Care".
2. ZZ pin is pulled down internally
3. For write cycles that following read cycles, the output buffers must be disabled with $\overline{OE}$, otherwise data bus contention will occur.
4. Sleep Mode means power down state of which stand-by current does not depend on cycle time.
5. Deselected means power down state of which stand-by current depends on cycle time.

TRUTH TABLES

SYNCHRONOUS TRUTH TABLE

$\overline{CS_1}$	CS_2	$\overline{CS_2}$	$\overline{ADSP}$	$\overline{ADSC}$	$\overline{ADV}$	$\overline{WRITE}$	CLK	ADDRESS ACCESSED	OPERATION
H	X	X	X	L	X	X	↑	N/A	Not Selected
L	L	X	L	X	X	X	↑	N/A	Not Selected
L	X	H	L	X	X	X	↑	N/A	Not Selected
L	L	X	X	L	X	X	↑	N/A	Not Selected
L	X	H	X	L	X	X	↑	N/A	Not Selected
L	H	L	L	X	X	X	↑	External Address	Begin Burst Read Cycle
L	H	L	H	L	X	L	↑	External Address	Begin Burst Write Cycle
L	H	L	H	L	X	H	↑	External Address	Begin Burst Read Cycle
X	X	X	H	H	L	H	↑	Next Address	Continue Burst Read Cycle
H	X	X	X	H	L	H	↑	Next Address	Continue Burst Read Cycle
X	X	X	H	H	L	L	↑	Next Address	Continue Burst Write Cycle
H	X	X	X	H	L	L	↑	Next Address	Continue Burst Write Cycle
X	X	X	H	H	H	H	↑	Current Address	Suspend Burst Read Cycle
H	X	X	X	H	H	H	↑	Current Address	Suspend Burst Read Cycle
X	X	X	H	H	H	L	↑	Current Address	Suspend Burst Write Cycle
H	X	X	X	H	H	L	↑	Current Address	Suspend Burst Write Cycle

Notes : 1. X means "Don't Care". 2. The rising edge of clock is symbolized by ↑.

3. $\overline{WRITE}$ = L means Write operation in WRITE TRUTH TABLE.
   $\overline{WRITE}$ = H means Read operation in WRITE TRUTH TABLE.
4. Operation finally depends on status of asynchronous input pins(ZZ and $\overline{OE}$).

WRITE TRUTH TABLE(x36)

$\overline{GW}$	$\overline{BW}$	$\overline{WEa}$	$\overline{WEb}$	$\overline{WEc}$	$\overline{WEd}$	OPERATION
H	H	X	X	X	X	READ
H	L	H	H	H	H	READ
H	L	L	H	H	H	WRITE BYTE a
H	L	H	L	H	H	WRITE BYTE b
H	L	H	H	L	L	WRITE BYTE c and d
H	L	L	L	L	L	WRITE ALL BYTEs
L	X	X	X	X	X	WRITE ALL BYTEs

Notes : 1. X means "Don't Care".

2. All inputs in this table must meet setup and hold time around the rising edge of CLK(↑).

WRITE TRUTH TABLE(x18)

$\overline{GW}$	$\overline{BW}$	$\overline{WEa}$	$\overline{WEb}$	OPERATION
H	H	X	X	READ
H	L	H	H	READ
H	L	L	H	WRITE BYTE a
H	L	H	L	WRITE BYTE b
H	L	L	L	WRITE ALL BYTEs
L	X	X	X	WRITE ALL BYTEs

Notes : 1. X means "Don't Care".

2. All inputs in this table must meet setup and hold time around the rising edge of CLK(↑).

PASS-THROUGH TRUTH TABLE

PREVIOUS CYCLE		PRESENT CYCLE				NEXT CYCLE
OPERATION	$\overline{WRITE}$	OPERATION	$\overline{CS_1}$	$\overline{WRITE}$	$\overline{OE}$	
Write Cycle, All bytes Address=An-1, Data=Dn-1	All L	Initiate Read Cycle Address=An Data=Qn-1 for all bytes	L	H	L	Read Cycle Data=Qn
Write Cycle, All bytes Address=An-1, Data=Dn-1	All L	No new cycle Data=Qn-1 for all bytes	H	H	L	No carryover from previous cycle
Write Cycle, All bytes Address=An-1, Data=Dn-1	All L	No new cycle Data=High-Z	H	H	H	No carryover from previous cycle
Write Cycle, One byte Address=An-1, Data=Dn-1	One L	Initiate Read Cycle Address=An Data=Qn-1 for one byte	L	H	L	Read Cycle Data=Qn
Write Cycle, One byte Address=An-1, Data=Dn-1	One L	No new cycle Data=Qn-1 for one byte	H	H	L	No carryover from previous cycle

Note : 1. This operation makes written data immediately available at output during a read cycle preceded by a write cycle.

ABSOLUTE MAXIMUM RATINGS*

PARAMETER	SYMBOL	RATING	UNIT
Voltage on V_{DD} Supply Relative to V_{SS}	V_{DD}	-0.3 to 4.6	V
Voltage on V_{DDQ} Supply Relative to V_{SS}	V_{DDQ}	V_{DD}	V
Voltage on Input Pin Relative to V_{SS}	V_{IN}	-0.3 to 4.6	V
Voltage on I/O Pin Relative to V_{SS}	V_{IO}	-0.3 to V_{DDQ}+0.5	V
Power Dissipation	P_D	1.6	W
Storage Temperature	T_{STG}	-65 to 150	°C
Operating Temperature	T_{OPR}	0 to 70	°C
Storage Temperature Range Under Bias	T_{BIAS}	-10 to 85	°C

***Note :** Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operating sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

OPERATING CONDITIONS at 3.3V I/O($0°C \le T_A \le 70°C$)

PARAMETER	SYMBOL	MIN	Typ.	MAX	UNIT
Supply Voltage	V_{DD}	3.135	3.3	3.465	V
	V_{DDQ}	3.135	3.3	3.465	V
Ground	V_{SS}	0	0	0	V

OPERATING CONDITIONS at 2.5V I/O($0°C \le T_A \le 70°C$)

PARAMETER	SYMBOL	MIN	Typ.	MAX	UNIT
Supply Voltage	V_{DD}	3.135	3.3	3.465	V
	V_{DDQ}	2.375	2.5	2.9	V
Ground	V_{SS}	0	0	0	V

CAPACITANCE*(T_A=25°C, f=1MHz)


PARAMETER	SYMBOL	TEST CONDITION	MIN	MAX	UNIT
Input Capacitance	C_{IN}	V_{IN}=0V	-	7	pF
Output Capacitance	C_{OUT}	V_{OUT}=0V	-	9	pF

***Note :** Sampled not 100% tested.

DC ELECTRICAL CHARACTERISTICS(V_{DD}=3.3V+0.165V/-0.165V, T_A=0°C to +70°C)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	MAX	UNIT	NOTES
Input Leakage Current(except ZZ)	I_{IL}	V_{DD} = Max ; V_{IN}=V_{SS} to V_{DD}		-2	+2	μA	
Output Leakage Current	I_{OL}	Output Disabled, V_{OUT}=V_{SS} to V_{DDQ}		-2	+2	μA	
Operating Current	I_{CC}	Device Selected, I_{OUT}=0mA, ZZ≤V_{IL} , Cycle Time ≥ t_{CYC} Min	-54	-	450	mA	1,2
			-60	-	420		
			-67	-	400		
			-72	-	380		
			-10	-	320		
Standby Current	I_{SB}	Device deselected, I_{OUT}=0mA, ZZ≤V_{IL}, f=Max, All Inputs≤0.2V or ≥ V_{DD}-0.2V	-54	-	130	mA	
			-60	-	120		
			-67	-	110		
			-72	-	90		
			-10	-	80		
	I_{SB1}	Device deselected, I_{OUT}=0mA, ZZ≤0.2V, f = 0, All Inputs=fixed (V_{DD}-0.2V or 0.2V)		-	30	mA	
	I_{SB2}	Device deselected, I_{OUT}=0mA, ZZ≥V_{DD}-0.2V, f=Max, All Inputs≤V_{IL} or ≥V_{IH}		-	30	mA	
Output Low Voltage(3.3V I/O)	V_{OL}	I_{OL}=8.0mA		-	0.4	V	
Output High Voltage(3.3V I/O)	V_{OH}	I_{OH}=-4.0mA		2.4	-	V	
Output Low Voltage(2.5V I/O)	V_{OL}	I_{OL}=1.0mA		-	0.4	V	
Output High Voltage(2.5V I/O)	V_{OH}	I_{OH}=-1.0mA		2.0	-	V	
Input Low Voltage(3.3V I/O)	V_{IL}			-0.3*	0.8	V	
nput High Voltage(3.3V I/O)	V_{IH}			2.0	V_{DD}+0.5**	V	3
Input Low Voltage(2.5V I/O)	V_{IL}			-0.3*	0.7	V	
Input High Voltage(2.5V I/O)	V_{IH}			1.7	V_{DD}+0.5**	V	3

Notes : 1. Reference AC Operating Conditions and Characteristics for input and timing.
2. Data states are all zero.
3. In Case of I/O Pins, the Max. V_{IH}=V_{DDQ}+0.3V.




TEST CONDITIONS


(V_{DD}=3.3V+0.165V/-0.165V,V_{DDQ}=3.3V+0.165/-0.165V or V_{DD}=3.3V+0.165V/-0.165V,V_{DDQ}=2.5V+0.4V/-0.125V, T_A=0to70°C)

PARAMETER	VALUE
Input Pulse Level(for 3.3V I/O)	0 to 3.0V
Input Pulse Level(for 2.5V I/O)	0 to 2.5V
Input Rise and Fall Time(Measured at 20% to 80% for 3.3V I/O)	1.0V/ns
Input Rise and Fall Time(Measured at 20% to 80% for 2.5V I/O)	1.0V/ns
Input and Output Timing Reference Levels for 3.3V I/O	1.5V
Input and Output Timing Reference Levels for 2.5V I/O	V_{DDQ}/2
Output Load	See Fig. 1

Output Load(A)



Output Load(B),
(for tLZC, tLZOE, tHZOE & tHZC)



* Including Scope and Jig Capacitance


Fig. 1

AC TIMING CHARACTERISTICS(VDD=3.3V+0.165V/-0.165V, TA=0°C to +70°C)


Parameter	Symbol	-54		-60		-67		-72		-10		Unit
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
Cycle Time	tCYC	5.4	-	6.0	-	6.7	-	7.2	-	10	-	ns
Clock Access Time	tCD	-	3.3	-	3.5	-	3.8	-	4.0	-	4.5	ns
Output Enable to Data Valid	tOE	-	3.3	-	3.5	-	3.8	-	4.0	-	4.5	ns
Clock High to Output Low-Z	tLZC	0	-	0	-	0	-	0	-	0	-	ns
Output Hold from Clock High	tOH	1.3	-	1.5	-	1.5	-	1.5	-	1.5	-	ns
Output Enable Low to Output Low-Z	tLZOE	0	-	0	-	0	-	0	-	0	-	ns
Output Enable High to Output High-Z	tHZOE	-	3.0	-	3.0	-	3.0	-	3.5	-	4.0	ns
Clock High to Output High-Z	tHZC	1.3	3.0	1.5	3.0	1.5	3.0	1.5	3.5	1.5	4.0	ns
Clock High Pulse Width	tCH	2.0	-	2.1	-	2.3	-	2.5	-	3.0	-	ns
Clock Low Pulse Width	tCL	2.0	-	2.1	-	2.3	-	2.5	-	3.0	-	ns
Address Setup to Clock High	tAS	1.5	-	1.5	-	1.5	-	1.5	-	1.5	-	ns
Address Status Setup to Clock High	tSS	1.5	-	1.5	-	1.5	-	1.5	-	1.5	-	ns
Data Setup to Clock High	tDS	1.5	-	1.5	-	1.5	-	1.5	-	1.5	-	ns
Write Setup to Clock High ($\overline{GW}$, $\overline{BW}$, $\overline{WE}$x)	tWS	1.5	-	1.5	-	1.5	-	1.5	-	1.5	-	ns
Address Advance Setup to Clock High	tADVS	1.5	-	1.5	-	1.5	-	1.5	-	1.5	-	ns
Chip Select Setup to Clock High	tCSS	1.5	-	1.5	-	1.5	-	1.5	-	1.5	-	ns
Address Hold from Clock High	tAH	0.5	-	0.5	-	0.5	-	0.5	-	0.5	-	ns
Address Status Hold from Clock High	tSH	0.5	-	0.5	-	0.5	-	0.5	-	0.5	-	ns
Data Hold from Clock High	tDH	0.5	-	0.5	-	0.5	-	0.5	-	0.5	-	ns
Write Hold from Clock High ($\overline{GW}$, $\overline{BW}$, $\overline{WE}$x)	tWH	0.5	-	0.5	-	0.5	-	0.5	-	0.5	-	ns
Address Advance Hold from Clock High	tADVH	0.5	-	0.5	-	0.5	-	0.5	-	0.5	-	ns
Chip Select Hold from Clock High	tCSH	0.5	-	0.5	-	0.5	-	0.5	-	0.5	-	ns
ZZ High to Power Down	tPDS	2	-	2	-	2	-	2	-	2	-	cycle
ZZ Low to Power Up	tPUS	2	-	2	-	2	-	2	-	2	-	cycle

Notes : 1. All address inputs must meet the specified setup and hold times for all rising clock edges whenever $\overline{ADSC}$ and/or $\overline{ADSP}$ is sampled low and CS is sampled low. All other synchronous inputs must meet the specified setup and hold times whenever this device is chip selected.
2. Both chip selects must be active whenever ADSC or ADSP is sampled low in order for the this device to remain enabled.
3. ADSC or ADSP must not be asserted for at least 2 Clock after leaving ZZ state.

TIMING WAVEFORM OF READ CYCLE




T MI G AV FO M F RT C CL




SAMSUNG ELECTRONICS


TIMING WAVEFORM OF COMBINATION READ/WRTE CYCLE(ADSP CONTROLLED , ADSC=HIGH)



TIMING WAVEFORM OF SINGLE READ/WRITE CYCLE($\overline{ADSC}$ CONTROLLED , $\overline{ADSP}$=HIGH)




TIMING WAVEFORM OF POWER DOWN CYCLE



APPLICATION INFORMATION


DEPTH EXPANSION

The Samsung 512Kx36 Synchronous Pipelined Burst SRAM has two additional chip selects for simple depth expansion. This permits easy secondary cache upgrades from 512K depth to 1M depth without extra logic.



INTERLEAVE READ TIMING (Refer to non-interleave write timing for interleave write timing)

(ADSP CONTROLLED , ADSC=HIGH)




***Notes :** n = 14 32K depth , 15 64K depth
16 128K depth , 17 256K depth
18 512K depth , 19 1M depth

Don't Care Undefined

APPLICATION INFORMATION


DEPTH EXPANSION

The Samsung 1Mx18 Synchronous Pipelined Burst SRAM has two additional chip selects for simple depth expansion. This permits easy secondary cache upgrades from 1M depth to 2M depth without extra logic.



INTERLEAVE READ TIMING (Refer to non-interleave write timing for interleave write timing)

(ADSP CONTROLLED , ADSC=HIGH)




***Notes :** n = 14 32K depth , 15 64K depth
16 128K depth , 17 256K depth
18 512K depth , 19 1M depth
20 2M depth


PACKAGE DIMENSIONS


100-TQFP-1420A

Units ; millimeters/Inches



119 BGA PACKAGE DIMENSIONS





NOTE :

1. All Dimensions are in Millimeters.
2. Solder Ball to PCB Offset : 0.10 MAX.
3. PCB to Cavity Offset : 0.10 MAX.