


ZWS150BAF-15/CO2



<b>Sales Region</b>	Worldwide
<b>Series</b>	ZWS-BAF
<b>Status</b>	Production
<b>Feature</b>	
<b>Option</b>	With coating on both sides of PCB model
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



**Electrical Characteristics**

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	89% Typ.
Rated Output Voltage[DC]	15V
Output Voltage Range[DC]	13.5 to 16.5V
Maximum Output Current	10A
Maximum Output Power	150W

**Cases Shape & Size**

Case'□ shape	PC board
Width(W)	75mm Nom.
Height(H)	37mm Nom.
Depth(D)	160mm Nom.
Weight	390g Typ.

**Other**

Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.