General Cable

# Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: C1703 Revision Level: 11/19/2012

**4C 14AWG 41/30BC PP, PVC** **COMMAND ® SERIES**

## A. CONSTRUCTION

| | | DIAMETERS |
|---|---|---|
| Conductor: | 14 AWG 41/30 BC | .071" nom |
| Insulation: | .009" Wall, Polypropylene (PP) | .089" nom |
| Cable Core: | 4C @ 6.00" LHL | .215" nom |
| Jacket: | .030" Polyvinyl Chloride (PVC) | .275" nom |
| Print Legend: | ***CAROL ® -- C1703 -- 4C 14AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8 CL3 60C -- CSA LL69381 AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA (Date code) (Seq Footage)*** | |

## B. INDUSTRY APPROVALS

| | |
|---|---|
| National Electrical Code | Article 725 |
| UL Standard 444 | Type CL3 |
| CSA International | Type AWM I/II A/B |

## C. ELECTRICAL PROPERTIES

| | |
|---|---|
| Temperature: | -20°C to +80°C |
| Suggested Working Voltage: | 600V Max |
| Conductor DCR: | 2.56 Ohms/M' @ 20°C (nom) |
| Mutual Capacitance: | 23.3 pF/ft @ 1kHz (nom) |

## D. COLOR CODE

| Item | COLOR |
|---|---|
| 1 | BLACK |
| 2 | RED |
| 3 | WHITE |
| 4 | GREEN |

## E. CUSTOMER APPROVAL

Signature: _____

Date: _____

Note: Data subject to change without notice. Contact your Customer Service representative for latest information.