

HSF RoHS

NOTES1:

UL Standard

1. Rated Voltage/Current : 300V / 27A
2. Withstanding Voltage : AC3000V/1Min.
3. Wire Range : 24~10AWG

NOTES2:

1. Dimension shall be interpreted per ASME Y14.5-2009
2. Pitch : 7.50mm, Poles : N=02-24P
3. Stripping length : 15-16 mm
4. Operating temperature : -40° C~+105° C
5. Undimensioned Tolerances:

P 距方向公差(mm)			其他尺寸公差(mm)					-	∩	∇
≤8	8 ~ 16	16 ~ 24	≤6	6 ~ 30	30 ~ 90	90 ~ 200	200 ~ 480	0.05/10		
±0.08	±0.13	±0.18	±0.10	±0.20	±0.30	±0.50	±0.70	±1'		

Ordering Information

JL 15CDGV- 381 XX G 0 1


Pitch
381=3.81PH

No. of pins
2P~24P

Housing Color
B=Black
G=Green
U=Blue
R=Red
W=White
Y=Yellow
O=Orange
E=Grey

Packing
O=Pe bag
A=Tray
T=Tube

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
A0		NEW		20.12.02



DRAW	LICHAO LIU	SCALE	FIT	JILN 东莞市锦凌电子有限公司 DONGGUAN JINLING ELECTRONIC CO.,LTD	
CHECK	LICHAO LIU	UNIT	mm		
APPROVE	YONGLIANG GAO	SIZE	A4		
		SHEET	1/1	PART NO.	JL15CDGV-381XXG01
		PROJ.		TITLE:	JL15CDGV-3.81-2P插拔式公座/绿色