



SPECIFICATION:

Current Rating: 3.0AMP
 Contact Resistance: 20m Ω (max)
 Insulation Resistance: 1000M Ω Min at 500V DC
 Dielectric Strength: 500V AC Per 1 Minute
 Operating Temperature: -40°C TO +105°C

MATERIALS:

Insulator: P.B.T.+30% Glass Fibre(UL 94V-0)
 Contact: Brass
 Contact plated: 0.8u" Gold Over Nickel

Poles	Part No.	Dimension mm		
		A	B	C
10	310R-10P	31.90	10.16	18.60
12	310R-12P	34.44	12.70	21.14
14	310R-14P	36.98	15.24	23.68
16	310R-16P	39.52	17.78	26.22
20	310R-20P	44.60	22.86	31.30
24	310R-24P	49.68	27.94	36.38
26	310R-26P	52.22	30.48	38.92
30	310R-30P	57.30	35.56	44.00
34	310R-34P	62.38	40.64	49.08
40	310R-40P	70.10	48.26	56.70
50	310R-50P	82.70	60.96	69.40
60	310R-60P	95.40	73.66	82.10
64	310R-64P	100.48	78.74	87.18

TOLERANCE TABLE	
.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	深圳市灿科盟实业有限公司 CHANKEMENG INDUSTRYCO., LTD	TITLE: 310R-XP			
CHECKED:	DATE:		CLIENT P/N	/	SCALE	free
DRAWN: LYF	DATE: 2008-04-07	UNIT	mm	REV.	A	
		FILE NO.	Ckmtw-310-00003			