

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

CM

00

Z

REVISED PER ECO-12-007492

03AUG12

KH

SM

1

MATERIAL: CONNECTOR - NYLON UL94V-2 .
CONTACTS - 0.30[.012] THICK COPPER ALLOY
BRIGHT TIN-LEAD .00203[.000080] MIN THICKNESS
FOR 640442-2 THRU 2-640442-8.
MATTE WHISKER MITIGATED TIN .00203[.000080] MIN THICKNESS
OVER NICKEL UNDERPLATE FOR 3-640442-2 THRU 5-640442-8.

2

CONTACTS ACCEPT 26 AWG WIRE WITH 1.52[.060] MAX
INSULATION DIAMETER.

3

CONTACTS MUST ACCEPT 0.64±0.03[.025±.001]
POST AND REMAIN LOCKED IN POSITION.

4

IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY
NOT APPEAR ON ALL ASSEMBLIES.

5

DIMENSIONS IN BRACKETS ARE IN INCHES.

6

HOUSING FEATURES ARE: CLOSED END WITH LOCKING RAMP

7

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8

BLUE COLOR STRIPE ON HOUSING (NOT SHOWN) MAY RUN DOWN BETWEEN RIBS.

YES

71.12[2.800]

28

5-640442-8

YES

68.58[2.700]

27

5-640442-7

YES

66.04[2.600]

26

5-640442-6

YES

63.50[2.500]

25

5-640442-5

YES

60.96[2.400]

24

5-640442-4

YES

58.42[2.300]

23

5-640442-3

YES

55.88[2.200]

22

5-640442-2

YES

53.34[2.100]

21

5-640442-1

YES

50.80[2.000]

20

5-640442-0

YES

48.26[1.900]

19

4-640442-9

YES

45.72[1.800]

18

4-640442-8

YES

43.18[1.700]

17

4-640442-7

YES

40.64[1.600]

16

4-640442-6

YES

38.10[1.500]

15

4-640442-5

YES

35.56[1.400]

14

4-640442-4

YES

33.02[1.300]

13

4-640442-3

YES

30.48[1.200]

12

4-640442-2

YES

27.94[1.100]

11

4-640442-1

YES

25.40[1.000]

10

4-640442-0

YES

22.86[.900]

9

3-640442-9

YES

20.32[.800]

8

3-640442-8

YES

17.78[.700]

7

3-640442-7

YES

15.24[.600]

6

3-640442-6

YES

12.70[.500]

5

3-640442-5

YES

10.16[.400]

4

3-640442-4

YES

7.62[.300]

3

3-640442-3

YES

5.08[.200]

2

3-640442-2

NO

71.12[2.800]

28

2-640442-8

SUPERCEDED BY 5-640442-8

NO

68.58[2.700]

27

2-640442-7

SUPERCEDED BY 5-640442-7

NO

66.04[2.600]

26

2-640442-6

SUPERCEDED BY 5-640442-6

NO

63.50[2.500]

25

2-640442-5

SUPERCEDED BY 5-640442-5

NO

60.96[2.400]

24

2-640442-4

SUPERCEDED BY 5-640442-4

NO

58.42[2.300]

23

2-640442-3

SUPERCEDED BY 5-640442-3

NO

55.88[2.200]

22

2-640442-2

SUPERCEDED BY 5-640442-2

NO

53.34[2.100]

21

2-640442-1

SUPERCEDED BY 5-640442-1

NO

50.80[2.000]

20

2-640442-0

SUPERCEDED BY 5-640442-0

NO

48.26[1.900]

19

1-640442-9

SUPERCEDED BY 4-640442-9

NO

45.72[1.800]

18

1-640442-8

OBSOLETE

NO

43.18[1.700]

17

1-640442-7

NO

40.64[1.600]

16

1-640442-6

NO

38.10[1.500]

15

1-640442-5

NO

35.56[1.400]

14

1-640442-4

NO

33.02[1.300]

13

1-640442-3

NO

30.48[1.200]

12

1-640442-2

NO

27.94[1.100]

11

1-640442-1

SUPERCEDED BY 4-640442-1

NO

25.40[1.000]

10

1-640442-0

NO

22.86[.900]

9

640442-9

NO

20.32[.800]

8

640442-8

NO

17.78[.700]

7

640442-7

NO

15.24[.600]

6

640442-6

NO

12.70[.500]

5

640442-5

NO

10.16[.400]

4

640442-4

NO

7.62[.300]

3

640442-3

NO

5.08[.200]

2

640442-2

LEADFREE

DIM A

NO. OF CIRCUITS

PART NO.

AMP

1

2

3

6.99
[.275]

6.22
[.245]

13.21
[.520]

6.99
[.275]

1.91
[.075]

1.42±0.10
[.056±.004]

4.67±0.08
[.184±.003]

3.66±0.08
[.144±.003]

A

+0.38
-0.25

A

+0.015
-0.010

2.54
[.100]
TYP

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0 PLC

±

1 PLC

±

2 PLC

±

3 PLC

± 0.13 [0.005]

4 PLC

±

ANGLES

±

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

FINISH

1

DWN

S. CARPENTER

10JUN2003

CHK

D. BOSSI

10JUN2003

APVD

D. BOSSI

10JUN2003

PRODUCT SPEC

108-1050

APPLICATION SPEC

114-1019

WEIGHT

CUSTOMER DRAWING

TE Connectivity

NAME

MTA 100 CONNECTOR ASSEMBLY,
26 AWG, STANDARD

SIZE

A2

CAGE CODE

00779

DRAWING NO

C=640442

RESTRICTED TO

-

SCALE

5:1

SHEET

1 of 1

REV

Z

1471-9 (3/11)