



Main

| | |
|---------------------------|--|
| Range of product | Harmony XVR |
| Product or component type | Prewired rotating mirror beacon |
| Sound signalling | Without |
| Device short name | XVR |
| Mounting diameter | 130 mm |
| IP degree of protection | IP66 conforming to IEC 60529 IP67 conforming to IEC 60529 |
| [Us] rated supply voltage | 120 V AC |
| Light source | High luminosity LED, red |

Complementary

| | |
|--|---|
| Material | ABS (acrylonitrile butadiene-styrene): body part PC: globe |
| CAD overall width | 130 mm |
| CAD overall depth | 130 mm |
| Net weight | 0.99 kg |
| Marking | CE |
| Product mounting | By 3 M6 screws |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Current consumption | 42 mA |
| Flashing frequency | 2.7 Hz |
| Clamping connection capacity | 1.25 mm ² |
| AWG gauge | AWG 18 |
| Cable length | 400 mm |

Environment

| | |
|-----------|------------------|
| Standards | EN/IEC 60947-5-1 |
|-----------|------------------|

| | |
|---------------------------------------|----------------------------------|
| Protective treatment | TC |
| Ambient air temperature for storage | -35...70 °C |
| Ambient air temperature for operation | -30...50 °C |
| Electrical shock protection class | Class II conforming to IEC 61140 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 1.328 kg |
| Package 1 Height | 30.5 cm |
| Package 1 width | 20 cm |
| Package 1 Length | 20 cm |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 6 |
| Package 2 Weight | 9.21 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 40 cm |
| Package 2 Length | 60 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |



Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Rotating Mirror Beacon

Dimensions

mm
in.



Rotating Mirror Beacon

Panel Cut-out

