


XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB201209-600-3A				Rev: A/3		
DIMENSION : (m/m) <div style="text-align: center; margin: 10px 0;">  </div>				A	Ø2.0±0.2	m/m
				B	1.2±0.2	m/m
				C	0.9±0.2	m/m
				D	0.5±0.3	m/m
				E		m/m
				F		m/m
				G		m/m
				H		m/m
				I		m/m
				J		m/m
				K		m/m
				L		m/m
				M		m/m
				N		m/m
				O		m/m
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS		
Z	60 Ohms±25% 90 Ohms Typ	TEST FREQ.	100 500	MHz	<input type="radio"/> HP 34401A MULTIMETER <input type="radio"/> HP 4195 NETWORKS/SPECTRUM ANALYZER <input type="radio"/> HP 42841 BIAS CURRENT SOURCE <input type="radio"/> HP 4285A LCR METER <input type="radio"/> HP 4286A RF LCR METER <input checked="" type="radio"/> HP 4291A RF IMPEDANCE / MATERIAL ANALYZER <input type="radio"/> HP 4338A MILLION OHM METER <input type="radio"/> HP 6632A DC POWER SUPPLY <input type="radio"/> HP4284A PRECISION LCR METER	
Rdc	0.025 Ohms Max	TEST FREQ.		MHz		
Idc	3000mA Max	TEST FREQ.		MHz		
Notes: <ol style="list-style-type: none"> 1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability. 2. Flammability: UL94V-0 3. ASTM oxygen index: > 28% 4. Insulation System: Class F 155°C, UL file E151556 5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C 6. Storage Temperature Range: -55°C to +125°C 7. Aqueous wash compatible 8. SMD Lead Coplanarity: ±0.004"(0.102mm) 9. Electrical and mechanical specifications 100% tested 10. RoHS Compliant Component 						
DRAWN BY :		CHECKED BY :		APPROVED BY :		
BW		TONY IMBURGIA		JOE HUFF		
				6-22-07		