
Schottky Rectifier
Module Type 60 A

V_{RRM} = 45 V

$I_{F(AV)}$ = 60 A

Features

- High Surge Capability
- Type 45 V V_{RRM}
- Isolation Type Package
- Electrically Isolated Base Plate
- Not ESD Sensitive



SOT-227 Package



RoHS COMPLIANT

REACH COMPLIANCE

Maximum ratings

Parameter	Symbol	Conditions	Value	Unit
Maximum recurrent peak reverse voltage	V_{RRM}		45	V
Maximum DC blocking voltage	V_{DC}		45	V
Maximum RMS Voltage	V_{RMS}		32	V
Operating temperature	T_j		-40 to 150	°C
Storage temperature	T_{stg}		-40 to 150	°C

Electrical characteristics at 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Average forward current (per pkg)	$I_{F(AV)}$	T_C = 110 °C	60	A
Peak forward surge current (per leg)	I_{FSM}	8.3 ms, half sine	500	A
Maximum instantaneous forward voltage* (per leg)	V_F	I_{FM} = 30 A, T_j = 25 °C	0.70	V
		I_{FM} = 30 A, T_j = 125 °C	0.66	V
Maximum instantaneous reverse current at rated DC blocking voltage (per leg)	I_R	T_j = 25 °C	1	mA
		T_j = 100 °C	10	mA
		T_j = 150 °C	30	mA
Isolation voltage	V_{iSO}	A.C. 1 minute	2500	V

Thermal characteristics

Maximum thermal resistance junction to case (per leg)	$R_{\Theta jc}$		1.20	°C/W

* Pulse Test: Pulse width 300 µs, Duty < 2 %

Figure.1 - Typical Forward Characteristics





Figure .2- Forward Derating Curve



Figupre.3 - Peak Forward Surge Current






Figure.4 - Typical Reverse Characteristics



Package dimensions and terminal configuration

Product is marked with part number and terminal configuration.



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	.500	.519	12.70	13.20
B	.307	.322	7.80	8.20
C	.029	.033	.75	.84
D	.077	.082	1.95	2.10
E	1.487	1.502	37.80	38.20
F	1.250	1.258	31.75	32.00
G	.931	.956	23.65	24.30
H	.996	1.007	25.30	25.60
I	.586	.594	14.90	15.10
J	.492	.516	12.50	13.10
K	.161	.169	4.10	4.30
L	.161	.169	4.10	4.30
M	.181	.191	4.60	4.95
N	.165	.177	4.20	4.50
O	1.184	1.192	30.10	30.30
P	M4*8			