# Plug-in bridge - FBS 1/3/5/7-8 - 3030396

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Plug-in bridge, pitch: 8.2 mm, width: 55.7 mm, number of positions: 7, pin assignment: 1, 3, 5, 7, color: red

RoHS

## Key Commercial Data

| | |
|---|---|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| GTIN | 4 055626 007359 |
| GTIN | 4055626007359 |

## Technical data

### Technical data

| | |
|---|---|
| Color | red |
| Material | Copper |
| Number of positions | 7 |
| Pin assignment | 1, 3, 5, 7 |
| Pitch | 8.2 mm |
| Height | 29.6 mm |
| Width | 55.7 mm |
| Flammability rating according to UL 94 | V0 |
| Maximum load current | 24 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |

### Standards and Regulations

| | |
|---|---|
| Flammability rating according to UL 94 | V0 |

### Environmental Product Compliance

| | |
|---|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

# Plug-in bridge - FBS 1/3/5/7-8 - 3030396

## Approvals

### Approvals

Approvals

EAC

Ex Approvals

### Approval details

| | | |
|---|---|---|
| EAC | EAC | RU C-DE.A*30.B.01742 |

Phoenix Contact 2019 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com