

2SB642

Silicon PNP epitaxial planer type


For low-power general amplification

Features

- High forward current transfer ratio h_{FE} .
- M type package allowing easy automatic and manual insertion as well as stand-alone fixing to the printed circuit board.

Absolute Maximum Ratings ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
Collector to base voltage	V_{CBO}	-60	V
Collector to emitter voltage	V_{CEO}	-50	V
Emitter to base voltage	V_{EBO}	-7	V
Peak collector current	I_{CP}	-200	mA
Collector current	I_C	-100	mA
Collector power dissipation	P_C	400	mW
Junction temperature	T_j	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 ~ +150	$^\circ\text{C}$



Electrical Characteristics ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector cutoff current	I_{CBO}	$V_{CB} = -20\text{V}, I_E = 0$			-1	nA
	I_{CEO}	$V_{CE} = -20\text{V}, I_B = 0$			-1	μA
Collector to base voltage	V_{CBO}	$I_C = -10\mu\text{A}, I_E = 0$	-60			V
Collector to emitter voltage	V_{CEO}	$I_C = -2\text{mA}, I_B = 0$	-50			V
Emitter to base voltage	V_{EBO}	$I_E = -10\mu\text{A}, I_C = 0$	-7			V
Forward current transfer ratio	h_{FE}^*	$V_{CE} = -10\text{V}, I_C = -2\text{mA}$	160		460	
Collector to emitter saturation voltage	$V_{CE(sat)}$	$I_C = -100\text{mA}, I_B = -10\text{mA}$			-1	V
Transition frequency	f_T	$V_{CB} = -10\text{V}, I_E = 2\text{mA}, f = 200\text{MHz}$		80		MHz
Collector output capacitance	C_{ob}	$V_{CB} = -10\text{V}, I_E = 0, f = 1\text{MHz}$		3.5		pF

* h_{FE} Rank classification

Rank	Q	R	S
h_{FE}	160 ~ 260	210 ~ 340	290 ~ 460

