


GENERAL PURPOSE APPLICATION.
SWITCHING APPLICATION.

FEATURES

- Low Leakage Current
: $I_{CEX} = -50\text{nA}(\text{Max.})$; $V_{CE} = -30\text{V}$, $V_{EB} = -0.5\text{V}$.
- Low Saturation Voltage
: $V_{CE(\text{sat})} = -0.4\text{V}(\text{Max.})$; $I_C = -150\text{mA}$, $I_B = -15\text{mA}$.
- Complementary to the KN2222/2222A.

MAXIMUM RATING (Ta=25 °C)

| CHARACTERISTIC | SYMBOL | RATING | | UNIT |
|-----------------------------|------------------|-----------|---------|------|
| | | KN2907 | KN2907A | |
| Collector-Base Voltage | V_{CBO} | -60 | | V |
| Collector-Emitter Voltage | V_{CEO} | -40 | -60 | V |
| Emitter-Base Voltage | V_{EBO} | -5 | | V |
| Collector Current | I_C | -600 | | mA |
| Collector Power Dissipation | P_C | 625 | | mW |
| Junction Temperature | T_j | 150 | | °C |
| Storage Temperature Range | T_{stg} | -55 ~ 150 | | °C |



KN2907/A


ELECTRICAL CHARACTERISTICS (Ta=25 °C)

| CHARACTERISTIC | | SYMBOL | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|--|---------------|---------------------------|------------------------------------|------|------|------|------|
| Collector Cut-off Current | | I_{CEX} | $V_{CE}=-30V, V_{EB}=-0.5V$ | - | - | -50 | nA |
| Collector Cut-off Current | KN2907 | I_{CBO} | $V_{CB}=-50V, I_E=0$ | - | - | -20 | nA |
| | KN2907A | | | - | - | -10 | |
| Collector-Base Breakdown Voltage | | $V_{(BR)CBO}$ | $I_C=-10\mu A, I_E=0$ | -60 | - | - | V |
| Collector-Emitter Breakdown Voltage * | KN2907 | $V_{(BR)CEO}$ | $I_C=-10mA, I_B=0$ | -40 | - | - | V |
| | KN2907A | | | -60 | - | - | |
| Emitter-Base Breakdown Voltage | | $V_{(BR)EBO}$ | $I_E=-10\mu A, I_C=0$ | -5 | - | - | V |
| DC Current Gain | KN2907 | $h_{FE(1)}$ | $I_C=-0.1mA, V_{CE}=-10V$ | 35 | - | - | |
| | KN2907A | | | 75 | - | - | |
| | KN2907 | $h_{FE(2)}$ | $I_C=-1.0mA, V_{CE}=-10V$ | 50 | - | - | |
| | KN2907A | | | 100 | - | - | |
| | KN2907 | $h_{FE(3)}$ | $I_C=-10mA, V_{CE}=-10V$ | 75 | - | - | |
| | KN2907A | | | 100 | - | - | |
| | KN2907 | $h_{FE(4)} *$ | $I_C=-150mA, V_{CE}=-10V$ | 100 | - | 300 | |
| | KN2907A | | | | | | |
| KN2907 | $h_{FE(5)} *$ | $I_C=-500mA, V_{CE}=-10V$ | 30 | - | - | | |
| KN2907A | | | 50 | - | - | | |
| Collector-Emitter Saturation Voltage * | | $V_{CE(sat)1}$ | $I_C=-150mA, I_B=-15mA$ | - | - | -0.4 | V |
| | | $V_{CE(sat)2}$ | $I_C=-500mA, I_B=-50mA$ | - | - | -1.6 | |
| Base-Emitter Saturation Voltage * | | $V_{BE(sat)1}$ | $I_C=-150mA, I_B=-15mA$ | - | - | -1.3 | V |
| | | $V_{BE(sat)2}$ | $I_C=-500mA, I_B=-50mA$ | - | - | -2.6 | |
| Transition Frequency | | f_T | $V_{CE}=-20V, I_C=-50mA, f=100MHz$ | 200 | - | - | MHz |
| Collector Output Capacitance | | C_{ob} | $V_{CB}=-10V, I_E=0, f=1MHz$ | - | - | 8 | pF |


* Pulse Test : Pulse Width $\leq 300 \mu s$, Duty Cycle $\leq 2\%$.

KN2907/A


$h_{FE} - I_C$



$C_{ob} - V_{CB}$



$V_{BE(sat)}, V_{CE(sat)} - I_C$



$P_c - T_a$

