
GS421SD


SURFACE MOUNT, SCHOTTKY BARRIER DIODE
VOLTAGE 40V, CURRENT 0.1A


Description

The GS421SD is designed for low power rectification.

Package Dimensions







REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	0.80	1.10	L1	0.42 REF.	
A1	0	0.10	L	0.15	0.35
A2	0.80	1.00	b	0.25	0.40
D	1.80	2.20	c	0.10	0.25
E	1.15	1.35	e	0.65 REF.	
HE	1.80	2.40	Q1	0.15 BSC.	

Absolute Maximum Ratings at T_A = 25℃


Parameter	Symbol	Ratings	Unit
Junction Temperature	Tj	+125	℃
Storage Temperature	Tstg	-40 ~ +125	℃
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	40	V
Maximum RMS Voltage	V_{RMS}	28	V
Maximum DC Blocking Voltage	V_{DC}	40	V
Peak Forward Surge Current at 8.3mSec single half sine-wave	I_{FSM}	1.0	A
Typical Junction Capacitance between Terminal (Note 1)	C_J	6.0	pF
Maximum Average Forward Rectified Current	Io	0.1	A
Total Power Dissipation	PD	225	mW


Electrical Characteristics (at T_A = 25℃ unless otherwise noted)


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Reverse Breakdown Voltage	$V_{(BR)R}$	40	-	-	V	IR=100μA
Maximum Instantaneous Forward Voltage	V_F	-	-	340	mV	IF1=10mA
		-	-	550		IF2=100mA
Maximum Average Reverse Current	I_R	-	-	30	uA	VR=10V


Notes: 1. Measured at 1.0 MHz and applied reverse voltage of 10 volts.
2. ESD sensitive product handling required.

Characteristics Curve









Important Notice:
- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:
- **Taiwan**: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
  TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China**: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
  TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165