
isc Silicon NPN Power Transistor KSD5017



DESCRIPTION


- High Breakdown Voltage-
  : V_{CBO}= 1500V (Min)
- High Switching Speed
- High Reliability

APPLICATIONS

- Designed for color TV horizontal output applicaitions

ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	1500	V
V_{CEO}	Collector-Emitter Voltage	800	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current- Continuous	6	A
I_{CP}	Collector Current-Peak	16	A
P_C	Collector Power Dissipation @ T_C=25℃	60	W
T_J	Junction Temperature	150	℃
T_{stg}	Storage Temperature Range	-55~150	℃



DIM	mm MIN	MAX
A	19.90	20.10
B	15.90	16.10
C	5.50	5.70
D	0.90	1.10
F	3.30	3.50
G	2.90	3.10
H	5.90	6.10
J	0.595	0.605
K	22.30	22.50
L	1.90	2.10
N	10.80	11.00
Q	4.90	5.10
R	3.75	3.95
S	3.20	3.40
U	9.90	10.10
Y	4.70	4.90
Z	1.90	2.10

isc Silicon NPN Power Transistor KSD5017

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	I_C= 5A; I_B= 1A			5.0	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	I_C= 5A; I_B= 1A			1.5	V
I_{CBO}	Collector Cutoff Current	V_{CB}= 800V ; I_E= 0			10	μA
I_{EBO}	Emitter Cutoff Current	V_{EB}= 5V ; I_C= 0			1	mA
h_{FE}	DC Current Gain	I_C= 1A ; V_{CE}= 5V	8			
f_T	Current-Gain—Bandwidth Product	I_C= 1A; V_{CE}= 10V		3		MHz
t_f	Fall Time	I_C= 5A , I_{B1}= 1A ; I_{B2}= -2A R_L= 40Ω ; V_{CC}= 200V			0.4	μs