Measurement condition

Ambient temperature: 23 °C
Input power level: 0 dBm
Terminating impedance: *
Input: 607 Ω || -1,7 pF
Output: 607 Ω || -1,7 pF
External Coil: 122 nH

Characteristics

Remark:
The reference level for the relative attenuation a_{rel} of the TFS 300 is the minimum of the pass band attenuation a_{min}. The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e. The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e. The nominal frequency f_N is fixed at 300,0 MHz without any tolerance. The given values for both the relative attenuation a_{rel} and the group delay ripple have to be achieved at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c.

D a t a		typ. value		tolerance / limit		
Insertion loss (reference level)	a_e	3,1		max.	6,5	dB
Nominal frequency	f_N	-			300,00	MHz
Centre frequency	f_C	300,01	MHz		-	
Passband	PB	-		f_N ±	70,0	kHz
Bandwidth	BW					
3 dB		306	kHz	min.	280	kHz
Relative attenuation	a_{rel}					
f_N ± 400 kHz		32	dB	min.	15	dB
f_N ± 400 kHz ... f_N ± 600 kHz		32	dB	min.	27	dB
f_N ± 600 kHz ... f_N ± 13 MHz		47	dB	min.	35	dB
f_N ± 100 MHz		60	dB	min.	58	dB
Group delay ripple within PB		0,9	µs	max.	2	µs
Input power level		-		max.	13	dBm
Operating temperature range	OTR	-		- 20 °C ... + 80°C		
Storage temperature range		-		- 30 °C ... + 85°C		
Frequency inversion temperature		+ 20	°C		-	
Temperature coefficient of frequency	TC_f **	-0.036	ppm/K²		-	

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.
**) $\Delta f(Hz) = TC_f(ppm/K^2) \times (T-T_0)^2 \times f_{To}(MHz)$


Generated:


Checked / Approved:

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.


Filter characteristic





Construction and pin connection


(All dimensions in mm)



1	Output
2	Ground
3	External Coil
4	Ground
5	Input
6	Ground
7	Ground
8	Ground

Date code:	Year + week
U	2006
V	2007
W	2008
...	

50 Ω Test circuit



Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics, reliability

After the following tests the filter shall meet the whole specification:


1. Shock:	500g, 1 ms, half sine wave, 3 shocks each plane; DIN IEC 68 T2 - 27
2. Vibration:	10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans; DIN IEC 68 T2 - 6
3. Change of temperature:	-55 °C to 125°C / 30 min. each / 10 cycles DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow):	reflow possible: three times max.; for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;

This filter is RoHS compliant (2002/95/EG, 2005/618/EG)

Packing


Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;

max. pieces of filters per reel:	3000
reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm



Tape (all dimensions in mm)

W	:	12,00 ± 0,3
Po	:	4,00 ± 0,1
Do	:	1,50 +0,1/-0
E	:	1,75 ± 0,1
F	:	5,50 ± 0,05
G(min)	:	0,75
P2	:	2,00 ± 0,05
P1	:	8,00 ± 0,1
D1(min)	:	1,50
Ao	:	5,30 ± 0,1
Bo	:	5,30 ± 0,1
Ct	:	9,5 ± 0,1



Reel (all dimensions in mm)

A	:330	
W1	: 12,4	+2/-0
W2(max)	: 18,4	
N(min)	: 50	
C	: 13,0	+0,5/-0,2

The minimum bending radius is 45 mm.


Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile



Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

History

Version	Reason of Changes	Name	Date
1.3	Add history. Change date code from month to week. Correct tape and reel information. Use harder test conditions for point stability characteristic.	Dr. Wall	28.03.2001
1.4	Use harder conditions for vibration and damp heat Add input power level	Herrler	30.07.2001
1.5	Change operating temperature range and relative attenuation Add filter characteristic	Strehl	15.05.2006
1.6	Add typical values	Dr. Wall	17.05.2006

Tele Filter GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.